



Almaredge™ 880

High performance semi-synthetic metalworking fluid

Description

Castrol Almaredge™ 880 (previously called Castrol Clearedge™ 880) is a high performance chlorinated semi synthetic metalworking fluid. It contains a blend of extreme pressure additives and corrosion inhibitors, which helps to enhance machining performance and surface finish, provide excellent product stability, improve system life and lower the overall operation costs.

Almaredge 880 is suitable for large central systems and single sump machines.

Application

Almaredge 880 is recommended for use on most general purpose machining applications including milling, drilling, tapping, and reaming. It is a versatile product that can be used for machining of cast iron, low-medium alloyed steel, high alloy-stainless steel and aluminium alloys.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow Metals
Grinding	ü ü	ü ü	ü ü	ü		ü
Miling, Turning (General Machining)	ü ü	ü ü	ü ü	ü		ü
Drilling	ü ü	ü ü	ü	ü		ü
Reaming, Tapping	ü ü	ü ü	ü			ü
Broaching	ü	ü				ü

Advantages

- Phenol and nitrite free to fulfil your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Excellent anti-corrosion properties to protect machine tools and parts
- Advanced extreme pressure additives to ensure improved tool life and part quality
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components
- Can be used on a wide range of metals and operations – an ideal candidate for product rationalization on the shop floor

Typical Characteristics

Name	Method	Units	Almaredge 880
<u>Concentrate</u>			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	20
<u>Emulsion</u>			
Appearance	Visual		Translucent
pH (5%)	DIN 51369 ASTM E 70-97		9.2
Refractometer Factor			1.5

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding	3-7%
General Machining	5-7%
Drilling	6-10%
Reaming and Tapping	6-12%
Broaching	7-12%
Water Range	50-400 ppm CaCO ₃

Additional Information

	Boron	Formaldehyde releasing agent	EP (S/P) - Ester	Amines	Chlorine
Additives	ü	ü		ü	ü

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called Clearedge 880. The name was changed in 2015.

Almaredge™ 880

12 May 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India
Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: customercare.india@castrol.com
www.castrol.com/industrial