

CRB Turbomax 15W-40 CH-4

For long and healthy engine life

Description

New Castrol CRB Turbomax 15W-40 CH-4 is an advanced heavy duty diesel engine oil, suitable for use in high speed 4-stroke diesel engines that use a broad range of fuel qualities.

Application

Castrol CRB Turbomax 15W-40 CH-4 is ideal for use in BS II and BS III compliant turbo charged commercial vehicles and all CH-4 recommended turbo-charged engines.

Advantages

Castrol CRB Turbomax 15W-40 CH-4 contains specially engineered DuraShield™ Boosters that help fight the main causes of engine damage. In severe testing, Castrol CRB Turbomax with DuraShield™ boosters delivers up to twice the engine life*.

Castrol CRB Turbomax with DuraShield™ boosters is proven in industry testing to help provide protection to your engine in two ways:

1. Under severe engine operating conditions soot can agglomerate to form large particles which help to displace oil on moving metal surfaces. This results in metal to metal contact. Castrol CRB Turbomax with DuraShield™ boosters helps to prevent the agglomeration of soot as well as protecting surfaces from wear.
2. Castrol CRB Turbomax with DuraShield™ boosters provides a protective layer on the moving metal surfaces which resists break down, even under difficult conditions.

** Based on time between camshaft rebuilds in a severe Cummins ISB engine test vs. an equivalent oil without DuraShield.*



Typical Characteristics

Name	Method	Units	CRB Turbomax 15W-40 CH-4
Density @ 29.5C, Relative	ASTM D1298	-	0.863
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.6
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	5500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	110
Viscosity Index	ASTM D2270	None	137
Ash, Sulphated	ASTM D874	% wt	1.12
Total Base Number, TBN	ASTM D2896	mg KOH/g	8.4
Flash Point, closed cup	ASTM D93	°C	205
Pour Point	ASTM D97	°C	-36

Product Performance Claims

API CH-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Turbomax 15W-40 CH-4

13 Dec 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customer-care.india@castrol.com