



Hyspin AWS Superclean Range

Anti-wear hydraulic oil

Description

The Castrol Hyspin AWS™ superclean hydraulic oil range is based upon highly refined mineral oil enhanced with a stabilised zinc additive system, filtered to ISO 4406 - 16/14/11 (similar to NAS 6).

Application

Hyspin AWS has been specially formulated to provide good anti-wear and thermal stability performance using the very latest additive technology. The careful blend of additives with a high quality base stock ensures that Hyspin AWS has excellent hydrolytic and oxidative stability while exhibiting a minimal tendency to produce sludge and deposits. In addition, Hyspin AWS provides corrosion protection to ferrous and yellow metal components found within a hydraulic system. This range is designed for use in industrial hydraulic systems which require anti-wear protection. It is also suitable for other duties in which lubricants of high oxidation stability and lubrication performance are required, such as lightly loaded gears, variable speed units and bearings. The Hyspin AWS range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers. Hyspin AWS is classified as follows: DIN 51502 classification - HLP ISO 6743/4 - Hydraulic Oils Type HM Hyspin AWS grades meet the requirements (for appropriate viscosity grade) of: DIN 51524 Part 2 Cincinnati Lamb (Milacron) P 68-69-70 Denison (Parker Hannafin) HF-0 US Steel 126 & 127 Eaton (formerly Vickers) I-286-S & M-2950-S Bosch Rexroth RE90220

Advantages

- Good thermal and oxidative stability leads to longer operating life, reduction in lubricant costs and minimises deposit formation giving a cleaner system.
- Excellent anti-wear performance gives wear protection and reduces downtime from unscheduled maintenance.
- Good filterability characteristics (including in the presence of water) enables cost savings to be made from increased filter life and reduced maintenance.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Increased cleanliness for systems with very fine tolerances, for improved equipment life and equipment accuracy.

Typical Characteristics

Name	Method	Units	22	32	46	68	100	150
ISO Viscosity Grade	-	-	22	32	46	68	100	150
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	870	880	880	880	890	890
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	22	32	46	68	100	150
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	4.3	5.3	6.7	8.6	11.1	14.5
Viscosity Index	ISO 2909 / ASTM D2270	-	>95	>95	>95	>95	>95	>95
Pour Point	ISO 3016 / ASTM D97	°C/°F	-27/-17	-27/-17	-24/-11	-21/-6	-18/0	-15/5
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	10/0	10/0	10/0	10/0	10/0	10/0
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	205/ 401	210/ 410	215/ 419	225/ 437	225/ 437	230/ 446
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	170/ 338	200/ 392	200/ 392	220/ 428	220/ 428	220/ 428
Water Separation @ 54°C / 129°F (40/37/3)	ISO 6614 / ASTM D1401	min	10	15	15	15	-	-
Water Separation @ 82°C / 180°F (40/37/3)	ISO 6614 / ASTM D1401	min	-	-	-	-	15	20
Air Release @ 50°C / 122°F	ISO 9120 / ASTM D3427	min	4	4	8	8	12	18
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	-	11	12	12	12	12
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass	Pass	Pass	Pass	Pass	Pass
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass
Fluid Cleanliness	ISO 4406	-	16/14/ 11	16/14/ 11	16/14/ 11	16/14/ 11	16/14/ 11	16/14/ 11

Subject to usual manufacturing tolerances.

Hyspin AWS Superclean Range

12 May 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India

Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: customer-care.india@castrol.com

www.castrol.com/industrial