

**Product Data** 

#### Seamax 20W-40

Longer engine life for diesel engines

# **Description**

Castrol Seamax 20W-40 diesel engine oil is designed to provide excellent protection, especially at high engine temperatures, helping to ensure longer engine life. It is formulated specifically to meet the lubrication demands of fishing vessels.

### **Application**

Seamax 20W-40 is suitable for use in turbocharged and naturally aspirated engines operating on both gasoline or marine gas oil.

### **Advantages**

- · Outstanding protection against wear even at high temperature conditions
- · Maintains excellent oil pressure in older engines
- · Reduced oil consumption

### **Product Performance Claims**

API CF/SF

## **Typical Characteristics**

Name	Method	Units	Seamax 20W-40
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	14.4
Viscosity, CCS -15C	ASTM D5293	mPa.s (cP)	7500
Viscosity, Kinematic 40C	ASTM D445	mm²/s	122.8
Viscosity Index	ASTM D2270	None	117
Ash, Sulphated	ASTM D874	% wt	1.0
Total Base Number, TBN	ASTM D2896	mg KOH/g	7.1
Pour Point	ASTM D97	°C	-30
Density @ 15C	ASTM D4052	g/ml	0.891

#### **Storage**

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Seamax 20W-40 07 Jul 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine