



## Spheerol SX 2

Water resistant grease

### Description

Castrol Spheerol SX 2 is a calcium complex, extreme pressure grease, resistant to both fresh and salt water providing a high level of corrosion protection to bearings and other components operating in environments subject to water or salt spray.

Spheerol SX 2 is an excellent top dressing for wire ropes, readily providing lubrication between the strands as well as corrosion protection for external surfaces.

### Application

Plain & anti-friction bearings subject to water wash.  
Bushings and Pivots.  
Wire Ropes.

### Features and Benefits

- Excellent protection against corrosion.
- High resistance to sea and fresh water washing.
- Very good high temperature performance.
- Strong adhesion to surfaces.

### Additional Information

Whilst traditional ways of applying grease on wire ropes can be utilised, use of proprietary pressurised grease applicator in accordance with manufacturer's instructions may assist in applying the appropriate quantity of grease and may also help to protect the core of the wire rope

### Technical Data

Name	Method	Units	Spheerol SX 2
Appearance	Visual		Pale brown grease
NLGI Consistency			2
Base Oil Viscosity @ 40°C		mm <sup>2</sup> /s	180
Penetration, Worked 60 Cycles	ASTM D217	1/10 mm	265-295
Drop Point	IP 132	°C	>280
Operating Temperature, min/max		°C	-20/150
Four Ball Load Test, Weld Point	IP 239	kg	400

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

## Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 600C, exposed to hot sun or freezing conditions.

Spheerol SX 2  
25 Mar 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

**Australia** Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1854

**Dubai** City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

**Norway** Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43

**Singapore** Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

**United Kingdom** BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Amhall Business Park, Westhill. AB32 6FJ, UK.  
Customer Service Number +44 (0)1224 766900

**USA** 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157

