



Product Data Sheet

Castrol TranSynd

Fully Synthetic Automatic Transmission Fluid

Description

TranSynd™ is a premium, synthetic universal powershift and automatic transmission fluid with TES 295™ and TES 468™ approval. It can be recommended for all vehicles calling for Dexron® III / Mercon® ATF's suitable for bus and refuse vehicles with automatic transmissions.

Advantages

- Excellent thermal and oxidative stability means that the viscosity remains almost constant helping prevent deposits and oil thickening - this extends transmission life and avoids incorrect gear changing.
- Excellent transmission cleanliness under all conditions permits extended oil drain and decreased servicing.
- Excellent temperature reduction through reduced friction leads to longer oil and component life and permits extended drain and decreased servicing.
- Lower power input means fuel savings potential and reduced emissions.
- Optimised frictional characteristics gives smoother gear changing at all ambient temperatures and load conditions.
- Constant frictional properties improve driving comfort.
- Outstanding cold flow properties enables faster oil flow to all critical components (eg torque converter, friction plates, planetary wheels and brake bands) particularly during cold starts.
- More responsive and comfortable gear change. Minimises 'shift stock' when changing gear.
- Excellent shear stability properties helps retain full transmission performance over whole oil drain period.
- Optimal lubrication ensures constant level of comfort during gear changing.
- Good extreme pressure (EP) and anti-wear performance gives better transmission component protection leading to longer life.
- Very good seal performance helps avoid oil leakages, reducing repair costs.
- Free from chlorine and heavy metals for better environmental compatibility - easier waste oil disposal and recyclability.

Typical Characteristics

Name	Method	Units	TranSynd™
Density @ 15C, Relative	ASTM D4052	g/ml	0.848
Colour	Visual	-	Red
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	38
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.4
Viscosity Index	ASTM D2270	None	167
Flash Point, COC	ASTM D92	°C	235
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	8500
Pour Point	ASTM D97	°C	-63

Product Performance Claims

Allison TES 295,
Allison TES 468
MB-Approval 236.91
MB-Approval 238.22
ZF TE-ML 04D, 14C, 16M, 20C
Voith H55.6336.xx
Recommended for use where Dexron® III / Mercon® is required.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol TranSynd

18 Feb 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 4000093, India
Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800
Customer Service: www.castrol.co.in Email: customercare.india@castrol.com