



Product Data Sheet

Transmax Manual 80W-90

Manual Transmission Fluid

Description

Castrol Transmax Manual 80W-90 may be used in applications where API GL-4 performance is required.

Advantages

- Good thermal stability protects against deposit formation and oil thickening maintaining the life and performance of lubricant and transmission.
- Good antiwear and load carrying characteristics extend the life of components.
- Improved low temperature protection and gear shifts compared to monograde products.

Typical Characteristics

Name	Method	Units	Transmax Manual 80W-90
Density @ 15C, Relative	ASTM D1298	g/ml	0.89
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	132
Viscosity Index	ASTM D2270	None	101
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	129000
Pour Point	ASTM D97	°C	-33
Flash Point, COC	DIN EN ISO 2592	°C	238

Product Performance Claims

API GL-4

Transmax Manual 80W-90

27 Jul 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 4000093, India
Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800
Customer Service: www.castrol.co.in Email: customercare.india@castrol.com