

CA512/15-2



connectwell
THE RIGHT CONNECTION

Uninsulated Fork Type Shorting link

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

Rated Current	41 A
Torque	0.5 Nm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA512/15-2	Uninsulated Fork Type Shorting link 2 Pole	100
CA512/15-3	Uninsulated Fork Type Shorting link 3 Pole	100
CA512/15-4	Uninsulated Fork Type Shorting link 4 Pole	100

SUITABLE FOR

CSB3/N3U	M3 sized Stud Type Terminal Blocks, suitable for operation with screwdriver and nut driver.
CSB3/N3UL	M3 sized Stud Type Terminal Blocks, suitable for operation with screwdriver and nut driver.
STH3	6 sq. mm Stud Type Terminal Block - with captive nuts.
CSB3/N3USH	M3 sized Stud Type Hinge Terminal Blocks, suitable for operation with screwdriver and nut driver.
CBS3U	M3 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.