CA514/2-2





Insulated Removable Shorting Links

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION		
Torque	1.2 Nm	

ORDERING INFORMATION			
CAT. NO.	DESCRIPTION	STD. PACK	
CA514/2-2	Insulated Removable Shorting Link available in 2 Pole	100	
CA514/2-3	Insulated Removable Shorting Link available in 3 Pole	50	
CA514/2-4	Insulated Removable Shorting Link available in 4 Pole	50	

SUITABLE FOR		
CBDT4U	Disconnect and Test Terminal Blocks	
CDTTS	Disconnect and Test Terminal Blocks	
CBS5U	M5 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.	
CDTTS-SH	Disconnect and Test Terminal Blocks	
CSB4/N4USH	M4 sized Stud Type hinge Terminal Blocks, suitable for operation with screwdriver and nut driver.	
CSTSB4/N4	M4 sized Stud Type Terminal Blocks, suitable for operation with screwdriver and nut driver.	
CBS4U	M4 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.	
CMDT4SH	Disconnect and Test Terminal Blocks	
CSB4/N4U	M4 sized Stud Type Terminal Blocks, suitable for operation with screwdriver and nut driver.	
CSTSB5	M5 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.	
CMDT4	Disconnect and Test Terminal Blocks	
CSB5/N5U	M5 sized Stud Type Terminal Blocks, suitable for operation with screwdriver and nut driver.	
CSB5/N5USH	M5 sized Stud Type hinge Terminal Blocks, suitable for operation with screwdriver and nut driver.	
CSE5U	M5 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.	
CSTSB4	M4 sized Stud Type Terminal Blocks, suitable for operation with screwdriver.	