

CA716/2



connectwell
THE RIGHT CONNECTION

External Comb Type Shorting Link

External shorting links bridge potentials between terminal blocks, reducing wiring time. Adjacent or selected blocks within an assembly can be easily interconnected. Individual links may be removed for selective shorting. These are insulated and available in 2, 3, 4 and 10 pole versions. They are made of tin plated brass/copper. Comb Link must be tightened to the recommended torque specified to get a reliable connection.

PRODUCT SPECIFICATION

Rated Current	32 A
Torque	0.8 Nm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA716/2	External Comb Type Shorting Link available in 2 Pole	50
CA716/3	External Comb Type Shorting Link available in 3 Pole	50
CA716/4	External Comb Type Shorting Link available in 4 Pole	50
CA716/10	External Comb Type Shorting Link available in 10 Pole	20
CA716/5-3A	External Comb Type Shorting Link 3 pole alternate suitable for CB16/3H	50

SUITABLE FOR

CAFL4U	4 sq.mm Fuse Terminal Blocks
CAFL4UL	4 sq.mm Fuse Terminal Blocks with offline LED indication.
CB16	Ceramic Terminal Blocks for 10 sq.mm wire.
CAFL4UN	Fuse Terminal Blocks