



THE RIGHT CONNECTION

Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, 10 or 100 pole assemblies and are ready for immediate installation.

PRODUCT SPECIFICATION		
Rated Current	32 A	
Torque	0.4 Nm	

ORDERING INFORMATION				
CAT. NO.	DESCRIPTION		STD. PACK	
CA727/2	Pre Assembled Shorting Link assemblies with 2 poles		100	
CA727/3	Pre Assembled Shorting Links assemblies with 3 poles		100	
CA727/4	Pre Assembled Shorting Link assemblies with 4 poles		100	
CA727/10	Pre Assembled Shorting Links assemblies with 10 poles		10	
SUITABLE FOR				
CDL4U(I.S)		4 sq.mm Double Level Internally Shorted Terminal Blocks.		
CMT4		4 sq.mm Micro Terminal Blocks.		
ODL4UA		Stackable 4 sq.mm Offset Double Level Terminal Blocks.		
CDL4UEN1		4 sq.mm Terminal Blocks with Neon Lamp indicator.		

4 sq. mm Panel Mount Terminal Blocks.

4 sq.mm Double Level Terminal Blocks.

4 sq.mm Offset Double Level Terminal Blocks.

CMB4

CDL4U

ODL4U