

CA747/2



connectwell
THE RIGHT CONNECTION

Insulated Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, 10 or 100 pole assemblies and are ready for immediate installation. Insulated Preassembled internal Shorting link assemblies provide shock protection when installed on Terminal Blocks. Insulated pre assembled shorting link assemblies provide shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

Rated Current	32 A
Torque	0.4 Nm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA747/2	Pre assembled Shorting Link for 2 way shorting	100
CA747/3	Pre assembled Shorting Link for 3 way shorting	100
CA747/4	Pre assembled Shorting Link for 4 way shorting	100
CA747/10	Pre assembled Shorting Link for 10 way shorting	10

SUITABLE FOR

CMB4	4 sq. mm Panel Mount Terminal Blocks.
ODL4U	4 sq.mm Offset Double Level Terminal Blocks.
CDL4U	4 sq.mm Double Level Terminal Blocks.
CDL4U(I.S)	4 sq.mm Double Level Internally Shorted Terminal Blocks.
CMT4	4 sq.mm Micro Terminal Blocks.
ODL4UA	Stackable 4 sq.mm Offset Double Level Terminal Blocks.