CBB95



connectwell
THE RIGHT CONNECTION

95 sq.mm Stud Type Power Terminal Blocks

CBB series Terminal Blocks are preferred for application using wires of large cross section. The Wire is crimped to a ring / fork lug and is screwed on to the flat current bar of the Terminal Block.

TECHNICAL DATA	
Rated Voltage	1000 V
Rated Current	232 A
Tightening Torque	10 Nm
Housing Material	Polymide
Product Function	Feed Through
Wire Entry Orientation	Side
Mounting Possibility	DIN 35/DIN 35-15 Rail
Stud Size	M10
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA	
Conductor Cross Section Stranded min.	16 mm²
Conductor Cross Section Stranded max.	95 mm²
Conductor Cross Section AWG/Kcmil min	8 AWG
Conductor Cross Section AWG/Kcmil max	4/0 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	16 mm²
Conductor Cross Section Stranded with Ferrule/Lug max	95 mm²

DIMENSIONS	
Height with DIN 35 x 15 mm rail	54.5 mm
Height with DIN 35 x 7.5 mm rail	47.3 mm
Length	92 mm
Width (Thickness)	38 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CBB95	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Grey colour	10
CBB95R	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Red colour	10
CBB95Y	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Yellow colour	10
CBB95BU	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Blue colour	10
CBB95BK	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Black colour	10
CBB95GN	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Green colour	10
CBB95BR	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Brown colour	10
CBB95O	95 sq.mm Feed through Bolt/Nut Type Terminal Block in Orange colour	10

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CBB95W	95 sq.mm Feed through Bolt/Nut Type Terminal Block in White colour	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	PPCBB1	Partition Plate in Grey colour	50
	CA791/2	Permanent Shorting Link for 2 way shorting	10
	CA791/3	Permanent Shorting Link for 3 way shorting	10
	CA509/K16	Marking Tag Blank suitable for CTS35UNA / CGT35U Terminal Blocks	100
	CBBPC2/100	Protective cover is available in 100 mm Length	10
	CBBPC2/160	Protective cover is available in 160 mm Length	10
	CBBPC2/200	Protective cover is available in 200 mm Length	10
	CBBPC2/250	Protective cover is available in 250 mm Length	10

CONNECTWELL INDUSTRIES PVT. LTD. | D7, Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India - 421 204.
Tel.: +91 251 7120 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com | Website: www.connectwell.com

CBB95



connectwell
THE RIGHT CONNECTION

APPROVALS

RATINGS AS PER STANDARDS			
STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	8 AWG	8 AWG	16 mm²
Conductor Cross Section Stranded max.	4/0 AWG	4/0 AWG	95 mm²
Rated Voltage	600 V	600 V	1000 V
Rated Current	230 A	230 A	232 A
Tightening Torque	90 lb-in	90 lb-in	10 Nm

CONNECTWELL INDUSTRIES PVT. LTD. | D7, Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India - 421 204.
Tel.: +91 251 7120 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com | Website: www.connectwell.com