

No. of Phases		3	Noise Standard		IS:12065
Frame Designation		63	Duty		S1
Rated Output	kW	0.18	Insulation Class		F
	HP	0.25	Cooling IS:6362		IC411
No. of Poles		4	Terminal Box Details	Type	HM2GN
Rated Voltage		V 415		Terminal Size	M4
Rated Frequency		Hz 50		No. of Terminal	6
Rated Current		A 0.57		Max. cable size (Cu) mm ²	1x3Cx4.0
Rated Speed		rpm 1380	Bearing Data	DE	6201ZZ
Rated Torque		kgm 0.13		NDE	6201ZZ
Efficiency	Full load	% 64.7	Lubrication	Prelubricated	
	3/4 load	% 64.7		Life L10 (Direct coupled) hrs.	50,000
	1/2 load	% 61.0		Regreasing Time hrs.	-
Power factor	Full load	0.68		Lifting Eyebolt IS:4190	
	3/4 load	0.64	Motor Weight (approx) kg	7.5	
	1/2 load	0.54	Rotor GD ² kgm ²	0.0010	
Max. Temp. Rise (Res.) °C		70	Ambient Temp. °C		50
Acceleration Time sec.		-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection		Y			
Tropicalised? (Yes / No)		Yes	Voltage Variation ± %		10
I_{st} / I_r		5.0	Frequency Variation ± %		5
T_{st} / T_r		1.8	Combiend Variation ± %		10
T_{po} / T_r		2.0	Brake	Size	06
Locked rotor withstand time	Hot sec.	4		Torque Nm	4
	Cold sec.	8		Safety Factor	3.21
Reference Standard		IS:12615		Release time ms	35
Protection IS:4691		IP 54		Volts (DC) V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020