

No. of Phases		3	Noise Standard		IS:12065
Frame Designation		71	Duty		S1
Rated Output	kW	0.18	Insulation Class		F
	HP	0.25	Cooling IS:6362		IC411
No. of Poles		6	Terminal Box Details	Type	HM2GN
Rated Voltage		V 415		Terminal Size	M4
Rated Frequency		Hz 50		No. of Terminal	6
Rated Current		A 0.65		Max. cable size (Cu) mm <sup>2</sup>	1x3Cx4.0
Rated Speed		rpm 915	Bearing Data	DE	6202ZZ
Rated Torque		kgm 0.19		NDE	6202ZZ
Efficiency	Full load	% 56.6	Lubrication	Prelubricated	
	3/4 load	% 56.6		Life L10 (Direct coupled ) hrs.	50,000
	1/2 load	% 53.0		Regreasing Time hrs.	-
Power factor	Full load	0.68		Lifting Eyebolt IS:4190	
	3/4 load	0.59	Motor Weight (approx) kg	10.5	
	1/2 load	0.48	Rotor GD <sup>2</sup> kgm <sup>2</sup>	0.0033	
Max. Temp. Rise (Res.) °C		70	Ambient Temp. °C		50
Acceleration Time sec.		-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection		Y			
Tropicalised? (Yes / No)		Yes	Voltage Variation ± %		10
$I_{st} / I_r$		4.5	Frequency Variation ± %		5
$T_{st} / T_r$		1.8	Combiend Variation ± %		10
$T_{po} / T_r$		2.0	Brake	Size	06
Locked rotor withstand time	Hot sec.	5		Torque Nm	4
	Cold sec.	12		Safety Factor	2.13
Reference Standard		IS:12615		Release time ms	35
Protection IS:4691		IP 54		Volts (DC) V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2  
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020