

No. of Phases		3	Noise Standard		IS:12065
Frame Designation		132S	Duty		S1
Rated Output	kW	7.5	Insulation Class		F
	HP	10.0	Cooling IS:6362		IC411
No. of Poles		2	Terminal Box Details	Type	HM3GN
Rated Voltage		V 415		Terminal Size	M5
Rated Frequency		Hz 50		No. of Terminal	6
Rated Current		A 13.3		Max. cable size (Cu) mm <sup>2</sup>	2x3Cx10.0
Rated Speed		rpm 2925	Bearing Data	DE	6208ZZ
Rated Torque		kgm 2.50		NDE	6208ZZ
Efficiency	Full load	% 88.1	Lubrication	Prelubricated	
	3/4 load	% 88.1		Life L10 (Direct coupled ) hrs.	50,000
	1/2 load	% 85.0		Regreasing Time hrs.	-
Power factor	Full load	0.89		Lifting Eyebolt IS:4190	
	3/4 load	0.86	Motor Weight (approx) kg		66.5
	1/2 load	0.82	Rotor GD <sup>2</sup> kgm <sup>2</sup>		0.0583
Max. Temp. Rise (Res.) °C		70	Ambient Temp. °C		50
Acceleration Time sec.		-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection		D			
Tropicalised? (Yes / No)		Yes	Voltage Variation ± %		10
I <sub>st</sub> / I <sub>r</sub>		7.0	Frequency Variation ± %		5
T <sub>st</sub> / T <sub>r</sub>		2.2	Combiend Variation ± %		10
T <sub>po</sub> / T <sub>r</sub>		2.5	Brake	Size	14
Locked rotor withstand time	Hot sec.	5		Torque Nm	60
	Cold sec.	11		Safety Factor	2.45
Reference Standard		IS:12615		Release time ms	150
Protection IS:4691		IP 54		Volts (DC) V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2  
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020