

No. of Phases		3	Noise Standard		IS:12065
Frame Designation		180L	Duty		S1
Rated Output	kW	11.0	Insulation Class		F
	HP	15.0	Cooling IS:6362		IC411
No. of Poles		8	Terminal Box Details	Type	HM4GN
Rated Voltage		V 415		Terminal Size	M6
Rated Frequency		Hz 50		No. of Terminal	6
Rated Current		A 23.0		Max. cable size (Cu) mm ²	2x3Cx25.0
Rated Speed		rpm 727	Bearing Data	DE	6310ZZ
Rated Torque		kgm 14.74		NDE	6210ZZ
Efficiency	Full load	% 86.9	Lubrication	Prelubricated	
	3/4 load	% 86.9		Life L10 (Direct coupled) hrs.	50,000
	1/2 load	% 84.0		Regreasing Time hrs.	-
Power factor	Full load	0.77		Lifting Eyebolt IS:4190	
	3/4 load	0.68	Motor Weight (approx) kg	210.0	
	1/2 load	0.55	Rotor GD ² kgm ²	0.5949	
Max. Temp. Rise (Res.) °C		70	Ambient Temp. °C		50
Acceleration Time sec.		-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection		D			
Tropicalised? (Yes / No)		Yes	Voltage Variation ± %		10
I _{st} / I _r		6.0	Frequency Variation ± %		5
T _{st} / T _r		2.2	Combiend Variation ± %		10
T _{po} / T _r		2.4	Brake	Size	25
Locked rotor withstand time	Hot sec.	9		Torque Nm	400
	Cold sec.	20		Safety Factor	2.77
Reference Standard		IS:12615		Release time ms	500
Protection IS:4691		IP 54		Volts (DC) V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020