

No. of Phases		3	Noise Standard		IS:12065
Frame Designation		200L	Duty		S1
Rated Output	kW	18.5	Insulation Class		F
	HP	25.0	Cooling IS:6362		IC411
No. of Poles		6	Terminal Box Details	Type	HM5GN
Rated Voltage		V 415		Terminal Size	M8
Rated Frequency		Hz 50		No. of Terminal	6
Rated Current		A 35.6		Max. cable size (Cu) mm <sup>2</sup>	2x3Cx70.0
Rated Speed		rpm 975	Bearing Data	DE	6312
Rated Torque		kgm 18.48		NDE	6312
Efficiency	Full load	% 90.4	Lubrication	Mobil / Unirex N3	
	3/4 load	% 90.4		Life L10 (Direct coupled ) hrs.	50,000
	1/2 load	% 87.0		Regreasing Time hrs.	8,000
Power factor	Full load	0.80	Lifting Eyebolt IS:4190		M16
	3/4 load	0.75	Motor Weight (approx) kg	283.0	
	1/2 load	0.65	Rotor GD <sup>2</sup> kgm <sup>2</sup>	0.8605	
Max. Temp. Rise (Res.) °C		70	Ambient Temp. °C		50
Acceleration Time sec.		-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection		D			
Tropicalised? (Yes / No)		Yes	Voltage Variation ± %		10
I <sub>st</sub> / I <sub>r</sub>		7.0	Frequency Variation ± %		5
T <sub>st</sub> / T <sub>r</sub>		2.1	Combiend Variation ± %		10
T <sub>po</sub> / T <sub>r</sub>		2.5	Brake	Size	25
Locked rotor withstand time	Hot sec.	7		Torque Nm	400
	Cold sec.	16		Safety Factor	2.21
Reference Standard		IS:12615		Release time ms	500
Protection IS:4691		IP 54		Volts (DC) V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2  
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020