

No. of Phases		3	Noise Standard		IS:12065	
Frame Designation		200L	Duty		S1	
Rated Output	kW	30.0	Insulation Class		F	
	HP	40.0	Cooling IS:6362		IC411	
No. of Poles		2	Terminal Box Details	Type	HM5GN	
Rated Voltage		V		Terminal Size	M8	
Rated Frequency		Hz		No. of Terminal	6	
Rated Current		A		Max. cable size (Cu)	mm ² 2x3Cx70.0	
Rated Speed		rpm	2955	DE	6312	
Rated Torque		kgm	9.89	NDE	6312	
Efficiency	Full load	%	92.0	Bearing Data	Lubrication	Mobil / Unirex N3
	3/4 load	%	92.0		Life L10 (Direct coupled)	hrs. 50,000
	1/2 load	%	89.0		Regreasing Time	hrs. 3,500
Power factor	Full load		0.89		Lifting Eyebolt IS:4190	M16
	3/4 load		0.86	Motor Weight (approx)	kg 276.0	
	1/2 load		0.81	Rotor GD ²	kgm ² 0.4468	
Max. Temp. Rise (Res.)		°C	70	Ambient Temp.	°C 50	
Acceleration Time		sec.	-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection			D			
Tropicalised? (Yes / No)			Yes	Voltage Variation ±	% 10	
I_{st} / I_r			7.0	Frequency Variation ±	% 5	
T_{st} / T_r			2.3	Combiend Variation ±	% 10	
T_{po} / T_r			2.7	Brake	Size	20
Locked rotor withstand time	Hot	sec.	10		Torque	Nm 260
	Cold	sec.	23		Safety Factor	2.68
Reference Standard			IS:12615		Release time	ms 400
Protection IS:4691			IP 54		Volts (DC)	V 190
Vibration Standard			IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020