

No. of Phases		3	Noise Standard		IS:12065	
Frame Designation		250MX	Duty		S1	
Rated Output	kW	30.0	Insulation Class		F	
	HP	40.0	Cooling IS:6362		IC411	
No. of Poles		8	Terminal Box Details	Type	HM5GN	
Rated Voltage		V 415		Terminal Size	M8	
Rated Frequency		Hz 50		No. of Terminal	6	
Rated Current		A 60.7		Max. cable size (Cu) mm <sup>2</sup>	2x3Cx70.0	
Rated Speed		rpm 733	Bearing Data	DE	6315	
Rated Torque		kgm 39.86		NDE	6315	
Efficiency	Full load	% 89.8	Lubrication	Mobil / Unirex N3		
	3/4 load	% 89.8		Life L10 (Direct coupled )	hrs.	50,000
	1/2 load	% 88.0		Regreasing Time	hrs.	6,000
Power factor	Full load	0.77	Lifting Eyebolt IS:4190		M16	
	3/4 load	0.71	Motor Weight (approx)	kg	450.0	
	1/2 load	0.61	Rotor GD <sup>2</sup>	kgm <sup>2</sup>	2.5127	
Max. Temp. Rise (Res.)		°C 70	Ambient Temp.		°C 50	
Acceleration Time		sec. -	Overall Dimensions of Packed motor (LxBxH) (mm)			
Stator Connection		D				
Tropicalised? (Yes / No)		Yes	Voltage Variation ±		% 10	
$I_{st} / I_r$		6.0	Frequency Variation ±		% 5	
$T_{st} / T_r$		2.1	Combiend Variation ±		% 10	
$T_{po} / T_r$		2.3	Brake	Size	31	
Locked rotor withstand time	Hot	sec. 12		Torque	Nm	800
	Cold	sec. 28		Safety Factor	2.05	
Reference Standard		IS:12615		Release time	ms	500
Protection IS:4691		IP 54		Volts (DC)	V	190
Vibration Standard		IS:12075	Data subject to tolerance as per IS: 12615			

Remarks: (1) Efficiency Class : IE2  
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020