

No. of Phases		3	Noise Standard		IS:12065	
Frame Designation		132S	Duty		S1	
Rated Output	kW	5.5	Insulation Class		F	
	HP	7.5	Cooling IS:6362		IC411	
No. of Poles		4	Terminal Box Details	Type	HM3GN	
Rated Voltage		V		Terminal Size	M5	
Rated Frequency		Hz		No. of Terminal	6	
Rated Current		A		Max. cable size (Cu)	mm ² 2x3Cx10.0	
Rated Speed		rpm	1450	DE	6208ZZ	
Rated Torque		kgm	3.69	NDE	6208ZZ	
Efficiency	Full load	%	87.7	Bearing Data	Lubrication	Prelubricated
	3/4 load	%	87.7		Life L10 (Direct coupled)	hrs. 50,000
	1/2 load	%	86.0		Regreasing Time	hrs. -
Power factor	Full load		0.83		Lifting Eyebolt IS:4190	M10
	3/4 load		0.79	Motor Weight (approx)	kg 77.0	
	1/2 load		0.72	Rotor GD ²	kgm ² 0.0676	
Max. Temp. Rise (Res.)		°C	70	Ambient Temp.	°C 50	
Acceleration Time		sec.	-	Overall Dimensions of Packed motor (LxBxH) (mm)		
Stator Connection			D	-		
Tropicalised? (Yes / No)			Yes	Voltage Variation ±	% 10	
I _{st} / I _r			7.0	Frequency Variation ±	% 5	
T _{st} / T _r			2.4	Combiend Variation ±	% 10	
T _{po} / T _r			2.8	Brake	Size	18
Locked rotor withstand time	Hot	sec.	4		Torque	Nm 150
	Cold	sec.	9		Safety Factor	4.14
Reference Standard			IS:12615		Release time	ms 300
Protection IS:4691			IP 54		Volts (DC)	V 190
Vibration Standard			IS:12075	Data subject to tolerance as per IS: 12615		

Remarks: (1) Efficiency Class : IE2
(2) Motor Construction : TEFC

Prep.: SK

Chkd.: SPJ

Date: 07/05/2020

Date: 07/05/2020