

DLP U-PVC mini trunking systems

for cable distribution

■ Selection chart for DLP mini trunking

		Length		Junction elements			
			=			b	<u>B</u>
	WHITE	2 m	End cap	Internal angle	External angle	Flat angle	Flat junction
:	32 x 12.5	0300 15	0312 03	0302 51	0302 51	0302 53	0302 54
	32 x 16	0308 04	0312 07	0333 25	0333 25	0333 27	0333 30
	32 x 20	0300 17	0312 09	0302 71	0302 71	0302 73	0302 74


■ Carrying capacity

Cat.Nos without	Maximum X- section in mm²		Cable Ø max.			
partition		1.5 mm²	2.5 mm²	4 mm²	6 mm²	in mm
0300 15 32 x 12.5 mm	285	19	12	10	4	2 x 10
0308 04 32 x 16 mm	330	25	16	15	7	13
0300 17 32 x 20 mm	500	34	22	19	11	18



Cable-grip

It makes the installation easier and faster by containing all the wires inside the trunking body before the cover is clipped



Comfortable implementation

■ During installation, the conductors stay in place in the 1 compartment mini-trunking thanks to cable-grip membranes



Speed of installation

- Cable holding is integrated with the trunking (no staple to add)
- Easy conductors position
- Quick cover fitting

DLP U-PVC trunking system 32 x 12.5, 32 x 16 and 32 x 20 mini-trunking system





Wiring capacity chart (p. 458) Selection chart (p. 460-462)

White RAL 9010 Ville RAL 90 to Factory finish
Uniform grip and thickness throughout the length
System with independent cover
Conforms to NF C 68-104

Pack	Cat.Nos	Mini-trunking - 32 x 12.5 mm	Pack	Cat.Nos	Finishing accessories
80(1)	0300 15	Without central partition Length 2 m	10/500	0312 07	End cap right or left
		Finishing	10/100	0333 25	Changeable internal-external angle from 60° to 120°
		Finishing accessories	10/100	0333 27	Changeable flat angle from 85° to 95°
20/400	0312 03	End cap right or left			
10/100	0302 51	Changeable internal-external angle from 60° to 120°	10/200	0333 30	Flat junction
10/100	0302 53	Changeable flat angle from 85° to 95°			Mini-trunking - 32 x 20 mm
10/200	0302 54	Flat junction	50(1)	0300 17	Mini-trunking - 32 x 20 mm Without partition Length 2 m
					<u>+ II</u>
		Mini-trunking - 32 x 16 mm			Finishing accessories
60(1)	0308 04	Without central partition	10/200	0312 09	End cap right or left
		Length 2 m ↓ l	10/100	0302 71	Changeable internal-external angle from 60° to 120°
			10/100	0302 73	Changeable flat angle from 85° to 95°
			10/100	0302 74	Flat junction

⁽¹⁾Number of meters per pack