

Ekinoxe DBs

meter box,
per phase isolation kit & panel locks



6077 75



6077 76



6078 95




6014 70 G

Dimensions (p. 223)

Pack	Cat.Nos	Meter box
		Suitable for mounting DX ³ /Lexic metering products Possible to mount on the top of the DB Provision for mounting Ammeter/Voltmeter/Ammeter Selector Switch/ Voltmeter Selector Switch *IK 08
1	6077 75	For all DPX ³ MCCB IP 20 DB
1	6077 76	For all DPX ³ MCCB IP 43 DBs
1	6077 77	For all DPX ³ MCCB IP 54 DBs
		Per phase Isolation Kit To be used for converting ETPN DB to per phase Isolation DB
1	6078 90	PPI conversion kit for ETPN 4 way DB
1	6078 91	PPI conversion kit for ETPN 6 way DB
1	6078 92	PPI conversion kit for ETPN 8 way DB
1	6078 93	PPI conversion kit for ETPN 12 way DB
1	6078 94	PPI conversion kit for ETPN 16 way DB
		Panel locks
1	6078 95	Panel lock for IP 43 SPN DBs
1	6078 96	Panel lock for IP 54 SPN DBs
1	6078 97	Panel lock for IP 43 ETPN, VTPN, DPX ³ MCCB & Flexy DBs
1	6078 98	Panel lock for IP 54 ETPN, VTPN, DPX ³ MCCB & Flexy DBs
		Blanking plates
10	6014 70 G	Blanking plates

supply busbars - insulated



6070 02



6070 12



6070 22



6070 23

Pack	Cat.Nos	Pin type supply busbars
		100 A copper busbars with insulated sleeve
		SP I/C and SP O/G
		Max. no. of devices connected Number of 17.5 mm modules
1	4049 26	13 13
1	4049 37	57 57
		SPN I/C and SPN O/G
1	4049 38	6 12
1	4049 39	28 56
		TPN I/C and SPN O/G
3/30	4049 40	5 12
10	4049 41	27 56
		TP I/C and TP O/G
1	4049 42	4 12
1	4049 43	19 57
		FP I/C and FP O/G
3/30	4049 44	3 12
10	4049 45	14 56
		Fork type supply busbars
		100 A copper busbars with insulated sleeve
		SP I/C and SP O/G
1	4049 11	12 12
1	4049 12	57 57
		SPN I/C and SPN O/G
1	4049 14	28 56
		TP I/C and TP O/G
1	4049 17	4 12
1	4049 18	19 57
		FP I/C and FP O/G
10	4049 20	14 56
		Accessories for fork and pin type busbars
6	4049 89	End caps for SP
6	4049 90	End caps for DP & TP
20/840	4049 91	End caps for FP