

DPX³ 160 thermal magnetic

MCCBs from 16 to 160 A



4200 00

4200 10

4200 37

4201 57

Technical characteristics and tripping curves (p. 88-99)
Dimensions (p. 80)

MCCBs for switching, remote tripping and protection of low voltage electrical system
 Supplied with cage terminals 70 mm² max. (flexible cable) or 95 mm² max. rigid cable with accessories
 Can be fitted with accessories and DPX³ common auxiliares
 Conform to IEC 60947-2

Pack	Cat.Nos		MCCBs
			Thermal adjustable from 0.8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)
			Breaking capacity Icu 16 kA (400 V~)
	3P	4P	In (A)
1	4200 00	4200 10	16
1	4200 01	4200 11	25
1	4200 02	4200 12	40
1	4200 03	4200 13	63
1	4200 04	4200 14	80
1	4200 05	4200 15	100
1	4200 06	4200 16	125
1	4200 07	4200 17	160
			Breaking capacity Icu 25 kA (400 V~)
1	4200 40	4200 50	16
1	4200 41	4200 51	25
1	4200 42	4200 52	40
1	4200 43	4200 53	63
1	4200 44	4200 54	80
1	4200 45	4200 55	100
1	4200 46	4200 56	125
1	4200 47	4200 57	160
			Breaking capacity Icu 36 kA (400 V~)
1	4200 80	4200 90	16
1	4200 81	4200 91	25
1	4200 82	4200 92	40
1	4200 83	4200 93	63
1	4200 84	4200 94	80
1	4200 85	4200 95	100
1	4200 86	4200 96	125
1	4200 87	4200 97	160
			Breaking capacity Icu 50 kA (400 V~)
1	4201 20	4201 30	16
1	4201 21	4201 31	25
1	4201 22	4201 32	40
1	4201 23	4201 33	63
1	4201 24	4201 34	80
1	4201 25	4201 35	100
1	4201 26	4201 36	125
1	4201 27	4201 37	160

Pack	Cat.Nos		MCCBs with electronic earth leakage module
			Thermal adjustable from 0.8 to 1 In Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)
			Equipped with earth leakage module with LCD screen Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)
			Breaking capacity Icu 16 kA (400 V~)
		4P	In (A)
1	4200 30		16
1	4200 31		25
1	4200 32		40
1	4200 33		63
1	4200 34		80
1	4200 35		100
1	4200 36		125
1	4200 37		160
			Breaking capacity Icu 25 kA (400 V~)
1	4200 70		16
1	4200 71		25
1	4200 72		40
1	4200 73		63
1	4200 74		80
1	4200 75		100
1	4200 76		125
1	4200 77		160
			Breaking capacity Icu 36 kA (400 V~)
1	4201 10		16
1	4201 11		25
1	4201 12		40
1	4201 13		63
1	4201 14		80
1	4201 15		100
1	4201 16		125
1	4201 17		160
			Breaking capacity Icu 50 kA (400 V~)
1	4201 50		16
1	4201 51		25
1	4201 52		40
1	4201 53		63
1	4201 54		80
1	4201 55		100
1	4201 56		125
1	4201 57		160

Bold catalogue numbers are products normally available with Legrand (India) stockists.
Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.

Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) stockists in multiples of the same.