

DPX³ 250 thermal magnetic

MCCBs from 100 to 250 A



4202 05



4202 25

Technical characteristics and tripping curves (p. 50-56)
Dimensions (p. 43)

MCCBs for switching, remote tripping and protection of low voltage electrical system
 Supplied with insulated shileds, screw terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable with accessories
 Can be fitted with accessories and DPX³ common auxiliaires
 Conform to IEC 60947-2

Pack	Cat.Nos		MCCBs
			Thermal adjustable from 0.8 to 1 In Magnetic adjustable from 5 to 10 In
			Breaking capacity Icu 25 kA (400 V~)
	3P	4P	In (A)
1	4202 05	4202 15	100
1	4202 07	4202 17	160
1	4202 08	4202 18	200
1	4202 09	4202 19	250
			Breaking capacity Icu 36 kA (400 V~)
1	4202 35	4202 45	100
1	4202 37	4202 47	160
1	4202 38	4202 48	200
1	4202 39	4202 49	250
			Breaking capacity Icu 50 kA (400 V~)
1	4202 65	4202 75	100
1	4202 67	4202 77	160
1	4202 68	4202 78	200
1	4202 69	4202 79	250
			Breaking capacity Icu 70 kA (400 V~)
1	4206 05	4206 15	100
1	4206 07	4206 17	160
1	4206 08	4206 18	200
1	4206 09	4206 19	250

Pack	Cat.Nos	MCCBs with electronic earth leakage module
		Thermal adjustable from 0.8 to 1 In Magnetic adjustable from 5 to 10 In Equipped with earth leakage module with LCD screen Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)
		Breaking capacity Icu 25 kA (400 V~)
	4P	In (A)
1	4202 25	100
1	4202 27	160
1	4202 28	200
1	4202 29	250
		Breaking capacity Icu 36 kA (400 V~)
1	4202 55	100
1	4202 57	160
1	4202 58	200
1	4202 59	250
		Breaking capacity Icu 50 kA (400 V~)
1	4202 85	100
1	4202 87	160
1	4202 88	200
1	4202 89	250
		Breaking capacity Icu 70 kA (400 V~)
1	4206 25	100
1	4206 27	160
1	4206 28	200
1	4206 29	250