

# Arteor™

hotel equipment – square version  
data, audio, video sockets and USB power supplies



Cover plates selection chart (p. 292-293)  
Technical data (p. 273-280)

Pack	Cat.Nos		Data, audio and video sockets
	White	Magnesium	
20/200	<b>5734 28</b>	<b>5736 28</b>	<b>RJ 45 tool-less system - Cat. 6</b> UTP - 8 contacts 1 module 22.5 x 45 mm
10/100	<b>5734 74</b>	<b>5736 74</b>	UTP - 8 contacts 2 modules 45 x 45 mm
			<b>USB sockets</b> Used to bring connections closer to the user For connecting USB devices (scanner-printer, external hard disk) Connection via screw terminals cross-section 1 mm <sup>2</sup> Recommended cable: USB A max. cable length 5 m 1 module 22.5 x 45 mm
1/20	5722 75	5727 75	
			<b>2 x female RCA</b> For the stereo audio connection of any DVD drive, camera, video recorder, etc. type peripheral Recommended cable: 1 shielded audio pair 1 module 22.5 x 45 mm
1/20	5722 72	5727 72	
			<b>3 x female RCA</b> For the composite video and stereo audio connection of a DVD drive, camera, video recorder, video conference equipment etc. Recommended cable: 1 shielded audio pair + 1 x 3 mm mini-coaxial 1 module 22.5 x 45 mm
1/20	5722 73	5727 73	
			<b>Female 3.5 mm jack</b> For stereo audio connection from a portable source Recommended cable: 1 x 0.22 mm <sup>2</sup> shielded audio pair
1/20	5722 74	5727 74	Connection on screw terminals 1 module 22.5 x 45 mm

Pack	Cat.Nos		Audio and video sockets
	White	Magnesium	
			<b>Female HD 15</b> For VGA, XGA or VESA connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 81 Max. cable length 25 m (beyond this a VGA amplifier is recommended)
1/20	5722 82	5727 82	Connection on screw terminals 2 modules 45 x 45 mm
1/20	5722 79	5727 79	Solder connection 1 module 22.5 x 45 mm
1	<b>5720 97</b>	<b>5725 97</b>	Preterminated sockets Female HD15 - 1 module
			<b>HDMI</b> For digital high definition audio and video connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 80 2 modules 45 x 45 mm
1/20	5722 81	5727 81	
1	<b>5720 96</b>	<b>5725 96</b>	Preterminated sockets HDMI 1.4 - 1 module
			<b>S-Video socket (4-pin mini-DIN)</b> 1-gang Provides the YC video link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc 1 module 22.5 x 45 mm
1/40	5744 01	5744 51	
			<b>Female HD 15 + jack 3.5 mm</b> 2 modules 45 x 45 mm Square version
1/20	5722 88	5727 88	

Pack	Cat.Nos		USB power supplies
	White	Magnesium	
			For recharging portable devices Conform to IEC 62684-2011-01 Consumption in passive mode < 0.3 W 2P+E tap-off connection via 2.5 mm <sup>2</sup> screw terminals Supplied cordless
5/25	5720 78	5725 78	<b>Double USB charger - 5 V - 1500 mA</b> For fast-charging telephones, smartphones, MP3/MP4 players and tablet PC 2 modules 
10/100	5720 71	5725 71	<b>Single USB charger - 5 V - 750 mA</b> For Smartphone 1 module 

**Bold catalogue numbers** are products normally available with Legrand (India) stockists.  
**Cat.Nos that are not bold** - delivery within 4 - 8 weeks from the date of order.

**Bold packing quantity** is our mandatory packing. Orders to be placed by Legrand (India) stockists in multiples of the same.


# Arteor™ audio and video sockets



5737 73



5720 96



5727 85



5722 76



5720 97



5722 88



Cover plates selection chart (p. 292-295)  
Technical data (p. 275-280)

Pack	Cat.Nos		Audio and video sockets
	White	Magnesium	
1/20	5722 72	5727 72	<b>2 x female RCA</b> For the stereo audio connection of any DVD drive, camera, video recorder, etc. type peripheral Recommended cable: 1 shielded audio pair Square version 1 module 22.5 x 45 mm 
1/20	5732 72	5737 72	Round version 2 modules 45 x 45 mm 
			<b>3 x female RCA</b> For the composite video and stereo audio connection of a DVD drive, camera, video recorder, video conference equipment etc. Recommended cable: 1 shielded audio pair + 1 x 3 mm mini-coaxial Square version 1 module 22.5 x 45 mm 
1/20	5722 73	5727 73	Round version 2 modules 45 x 45 mm 
			<b>Female 3.5 mm jack - square version</b> For stereo audio connection from a portable source Recommended cable: 1 x 0.22 mm <sup>2</sup> shielded audio pair Connection on screw terminals 1 module 22.5 x 45 mm 
1/20	5722 74	5727 74	
1/20	5722 78	5727 78	Solder connection 1 module 22.5 x 45 mm 

Pack	Cat.Nos		Audio and video sockets (continued)
	White	Magnesium	
1/20	5722 81	5727 81	<b>HDMI</b> For digital high definition audio and video connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 80 2 modules 45 x 45 mm Square version 
1	<b>5720 96</b>	<b>5725 96</b>	Preterminated sockets HDMI 1.4 - 1 module 
1/20	5722 85	5727 85	Round version 
			<b>S-video sockets (4-pin mini-DIN)</b> 1-gang Provides the YC video link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc. Square version 1 module 22.5 x 45 mm 
1/20	5744 01	5744 51	
1/20	5745 01	5745 51	Round version 2 modules 45 x 45 mm 
			<b>Female BNC 75</b> For the composite video connection of any DVD drive, camera, video recorder, etc. Recommended cable: RG59 coaxial Max. cable length: 10 m 1 module 22.5 x 45 mm 
1/20	5722 76	5727 76	
			<b>Female HD 15</b> For VGA, XGA or VESA connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 81 Max. cable length 25 m (beyond this a VGA amplifier is recommended) Connection on screw terminals 2 modules 45 x 45 mm 
1/20	5722 82	5727 82	
1/20	5722 79	5727 79	Solder connection 1 module 22.5 x 45 mm 
1	<b>5720 97</b>	<b>5725 97</b>	Preterminated sockets Female HD15 - 1 module 

Pack	Cat.Nos		Female HD 15 + jack 3.5 mm
	White	Magnesium	
1/20	5722 88	5727 88	2 modules 45 x 45 mm Square version 
1/20	5722 89	5727 89	Round version 

## Audio/video preterminated sockets

# The right system to meet your needs

A wide range of technologies (HD15, HDMI, DISPLAY PORT, RCA, JACK) to suit the location and the user requirements

### INSTALLATION EXAMPLE WITH HD15 PRETERMINATED SOCKET AND VIDEO PROJECTOR SWITCH

**1** Quick installation

**2** Easy connection

**3** Optimum performance



**1** Infrared ON/STANDBY control for video projector associated with a pushbutton  
Cat.No 0787 99/5720 89

**2 3** Preterminated HD15 sockets  
Cat.No 0787 77/5720 97

**4** 10 m male/male HD15 cords  
Cat.No 0517 23

**5 6** Male/male HD 15 cords

## audio/video system

### audio/video sockets



Pack	Cat.Nos	Female HD15 sockets	HD15 + 3.5 mm Jack amplifier
1 1	Arteor <b>5720 97</b> 5725 97	Used to transmit analogue video streams (VGA, XGA, UXGA depending on graphic card) between a source (computer) and a compatible receiver (video projector, TV, etc) <b>Preterminated sockets - 1 module</b> Equipped with cord, length 15 cm ○ White ● Magnesium	Used to connect audio/video terminals more than 20 m apart up to 100 m The video link is via an HD15 connector (resolution up to UXGA) The stereo audio link is via a 3.5 mm Jack The kit includes: - one 4-module transmitter equipped with an HD15 connector and a 3.5 mm Jack - one 4-module receiver equipped with an HD15 connector and a 3.5 mm Jack - one 4-module power supply to be connected on the mains then linked to the receiver or transmitter The link between the transmitter and receiver is via a network cord RJ 45/RJ 45 ○ White
1 1	5722 82 5727 82	<b>Screw-type female HD15 sockets - 2 modules</b> ○ White ● Magnesium	
1 1	5722 88 5727 88	<b>Screw-type female HD15 sockets 2 modules + 3.5 mm Jack</b> ○ White ● Magnesium	
1 1	5722 79 5727 79	<b>Solder-type female HD15 sockets 1 module</b> 15 pin ○ White ● Magnesium	1 Arteor <b>5723 70</b>
1 1	Arteor <b>5720 96</b> 5725 96	<b>HDMI type A sockets</b> Used to transmit high-definition digital audio/video streams between a source (computer, HD-DVD drive, etc) and a compatible receiver (TV, video projector, etc) <b>Preterminated sockets HDMI 1.4 - 1 module</b> Equipped with cord, length 15 cm ○ White ● Magnesium	1 Arteor <b>5720 89</b> ○ White
1 1	5722 81 5727 81	<b>Screw-type sockets HDMI 1.3 - 2 modules</b> ○ White ● Magnesium	Used to transmit high-definition digital audio/video streams between a source (laptop, computer, etc.) and a compatible receiver (video projector, TV, etc.) <b>Preterminated socket - 1 module</b> Equipped with cord, length 15 cm ○ White ● Magnesium
1 1	Arteor <b>5720 91</b> 5725 91	<b>Jack sockets 3.5 mm</b> 3.5 mm Jack connectors can be used to create audio/video links <b>Preterminated sockets - 1 module</b> Equipped with cord, length 15 cm ○ White ● Magnesium	
1 1	5722 74 5727 74	<b>4 screw-type female 3.5 mm Jack socket - 1 module</b> ○ White ● Magnesium	
1 1	5722 78 5727 78	<b>Solder-type female 3.5 mm Jack socket - 1 module</b> ○ White ● Magnesium	1 Arteor <b>5720 90</b> 5725 90