

# Arteor™

hotel equipment – square version  
data, audio and video sockets



Cover plates selection chart (p. 262-265)  
Technical data (p. 244-248)

Pack	Cat.Nos		Data, audio and video sockets
	White	Magnesium	
<b>20/200</b>	<b>5734 28</b>	<b>5736 28</b>	<b>RJ 45 tool-less system - Cat. 6</b> UTP - 8 contacts 1 module 22.5 x 45 mm
<b>10/100</b>	<b>5734 74</b>	<b>5736 74</b>	UTP - 8 contacts 2 modules 45 x 45 mm
<b>1/20</b>	5722 75	5727 75	<b>USB sockets</b> Used to bring connections closer to the user For connecting USB devices (scanner-printer, external hard disk) Connection via screw terminals cross-section 1 mm <sup>2</sup> Recommended cable: USB A max. cable length 5 m 1 module 22.5 x 45 mm
<b>1/20</b>	5722 72	5727 72	<b>2 x female RCA</b> For the stereo audio connection of any DVD drive, camera, video recorder, etc. type peripheral Recommended cable: 1 shielded audio pair 1 module 22.5 x 45 mm
<b>1/20</b>	5722 73	5727 73	<b>3 x female RCA</b> For the composite video and stereo audio connection of a DVD drive, camera, video recorder, video conference equipment etc. Recommended cable: 1 shielded audio pair + 1 x 3 mm mini-coaxial 1 module 22.5 x 45 mm
<b>1/20</b>	5722 71	5727 71	<b>YUV</b> For analog high definition connection of a DVD, PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable: 3 x 3 mm mini-coaxial (max. cable length 25 m) or 3 x RG59 coaxial (max. cable length 50 m) 1 module 22.5 x 45 mm
<b>1/20</b>	5722 74	5727 74	<b>Female 3.5 mm jack</b> For stereo audio connection from a portable source Recommended cable: 1 x 0.22 mm <sup>2</sup> shielded audio pair Connection on screw terminals 1 module 22.5 x 45 mm

Pack	Cat.Nos		Audio and video sockets (continued)
	White	Magnesium	
<b>1/20</b>	5722 82	5727 82	<b>Female HD 15</b> For VGA, XGA or VESA connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 81 Max. cable length 25 m (beyond this a VGA amplifier is recommended) Connection on screw terminals 2 modules 45 x 45 mm
<b>1/20</b>	5722 79	5727 79	Solder connection 1 module 22.5 x 45 mm
<b>1/20</b>	5722 81	5727 81	<b>HDMI</b> For digital high definition audio and video connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 80 2 modules 45 x 45 mm
<b>1/40</b>	5744 01	5744 51	<b>S-Video socket (4-pin mini-DIN)</b> 1-gang Provides the YC video link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc 1 module 22.5 x 45 mm
<b>1/20</b>	5722 88	5727 88	<b>Female HD 15 + jack 3.5 mm</b> 2 modules 45 x 45 mm Square version

**Bold catalogue numbers** are products normally available with Legrand (India) stockists.

**Cat. nos. that are not bold** - delivery within 4 - 8 weeks from the date of order.

**Bold packing quantity** is our mandatory packing. Orders to be placed by Legrand (India) stockists in multiples of the same.

# Arteor™ audio and video sockets



Cover plates selection chart (p. 262-265)  
Technical data (p. 244-248)

Pack	Cat.Nos		Audio and video sockets	Pack	Cat.Nos		Audio and video sockets (continued)
1/20	5722 72	5727 72	<b>2 x female RCA</b> For the stereo audio connection of any DVD drive, camera, video recorder, etc. type peripheral Recommended cable: 1 shielded audio pair Square version 1 module 22.5 x 45 mm	1/20	5722 81	5727 81	<b>HDMI</b> For digital high definition audio and video connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 80 2 modules 45 x 45 mm Square version
1/20	5732 72	5737 72	Round version 2 modules 45 x 45 mm	1/20	5722 85	5727 85	Round version
1/20	5722 73	5727 73	<b>3 x female RCA</b> For the composite video and stereo audio connection of a DVD drive, camera, video recorder, video conference equipment etc. Recommended cable: 1 shielded audio pair + 1 x 3 mm mini-coaxial Square version 1 module 22.5 x 45 mm	1/20	5744 01	5744 51	<b>S-video sockets (4-pin mini-DIN)</b> 1-gang Provides the YC video link for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc. Square version 1 module 22.5 x 45 mm
1/20	5732 73	5737 73	Round version 2 modules 45 x 45 mm	1/20	5745 01	5745 51	Round version 2 modules 45 x 45 mm
1/20	5722 74	5727 74	<b>Female 3.5 mm jack - square version</b> For stereo audio connection from a portable source Recommended cable: 1 x 0.22 mm <sup>2</sup> shielded audio pair Connection on screw terminals 1 module 22.5 x 45 mm	1/20	5722 76	5727 76	<b>Female BNC 75</b> For the composite video connection of any DVD drive, camera, video recorder, etc. Recommended cable: RG59 coaxial Max. cable length: 10 m 1 module 22.5 x 45 mm
1/20	5722 78	5727 78	Solder connection 1 module 22.5 x 45 mm	1/20	5722 82	5727 82	<b>Female HD 15</b> For VGA, XGA or VESA connection of a PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable Cat.No 0327 81 Max. cable length 25 m (beyond this a VGA amplifier is recommended) Connection on screw terminals 2 modules 45 x 45 mm
1/20	5722 71	5727 71	<b>YUV - square version</b> For analog high definition connection of a DVD, PC monitor, plasma screen, video projector, graphic paintbox, etc. Recommended cable: 3 x 3 mm mini-coaxial (max. cable length 25 m) or 3 x RG59 coaxial (max. cable length 50 m) 1 module 22.5 x 45 mm 	1/20	5722 79	5727 79	Solder connection 1 module 22.5 x 45 mm
1/20	5722 88	5727 88	<b>Female HD 15 + jack 3.5 mm</b> 2 modules 45 x 45 mm Square version	1/20	5722 89	5727 89	Round version

**Bold catalogue numbers** are products normally available with Legrand (India) stockists.  
**Cat. nos. that are not bold** - delivery within 4 - 8 weeks from the date of order.

**Bold packing quantity** is our mandatory packing. Orders to be placed by Legrand (India) stockists in multiples of the same.