

# Arteor™

ventilation, heating, roller blinds control, RCBO and MCB



Support frame and plate selection charts **p. 398-405**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 397) and plates (p. 398 to 405)

Pack	Cat.Nos	Fan controllers	Pack	Cat.Nos	Electric roller blind controllers - 250 V~
		2 modules			<b>For control via automatic box (N/O mechanism)</b> Double push-button - 10 A 2 modules
1	5 722 17	<b>AC speed control - 4 positions</b> ○ White	10	5 722 19	○ White - square version
1	5 727 17	● Magnesium	10	5 727 19	● Magnesium - square version
		<b>Rotary speed controller for fan</b> Operates 40 to 400 VA limit switch For progressive speed control of ceiling fan	10	5 732 19	○ White - round version
1	5 722 18	○ White	10	5 737 19	● Magnesium - round version
1	5 727 18	● Magnesium			<b>For direct control of a motor (mechanism with fixed positions)</b> Double push-button - 10 A 2 modules
5	5 722 15	<b>Fan step regulator - 100 W</b> ○ White	10	5 722 20	○ White - square version
5	5 727 15	● Magnesium	10	5 727 20	● Magnesium - square version
		<b>Thermostats</b>	10	5 732 20	○ White - round version
		<b>Electronic room thermostat</b> Control knob with index and adjustable segments for min. and max. settings Adjustable range from 5 °C to 30 °C (+/- 0.5 °C) Power supply: 230 V~ - 50/60 Hz One potential free changeover contact output Suitable for controlling heated ceilings and underfloor heating - LV use breaking capacity: 8 A - 250 V~ - resistive inductive circuit 2 A - 250 V~ - inductive circuit - ELV use breaking capacity: 12 to 48 V~ - 12 to 24 V=, from 1 mA min. to 500 mA max.	10	5 737 20	● Magnesium - round version
1	5 722 03	2 modules ○ White			<b>RCBO - 16 A - 230 V~</b> Single pole + Neutral - 30 mA - 2 modules The RCBO is used to protect people (premises with a conductive floor, presence of water, etc...) against direct contact with live parts or leakages to earth With test button ○ White
1	5 727 03	● Magnesium	1	5 723 60	
		<b>Thermostat for electric floor heating</b> With one potential free N/O contact and LED 16 A - 230 V~ Adjustable range from 10 °C to 60 °C 2 modules			<b>Thermal magnetic proximity MCB</b> Single pole + Neutral - 230 V~ - 16 A Used for local protection of part in a circuit (e.g. 2P+E socket) against overloads and short-circuits Main protection being close to the user plus discriminating allows immediate reset Can also be used as a local consumption limiter (depending on its rating) Breaking capacity: 3000 A - 2 modules ○ White
1	5 722 63	○ White	1	5 723 61	
1	5 727 63	● Magnesium			
		<b>Curtain switches</b>			
		1 module			
5	5 722 02	<b>Curtain switch centre off</b> ○ White			
5	5 727 02	● Magnesium			
5	5 722 01	<b>Curtain switch centre retract</b> ○ White			
5	5 727 01	● Magnesium			