


COMMERCIAL LED LIGHTING

' SLEEK SQ ' Sleek square recess mounting LED downlight BGSLO Sleek 4/8/15W WH SQ





NOMINAL DIMENSIONS IN mm Tolerance +/-5

Cat. Ref.	A Sq.	B Sq.	Height - C
BGSLO Sleek 4W WH SQ	107	90	22
BGSLO Sleek 8W WH SQ	120	103	22
BGSLO Sleek 15W WH SQ	200	173	22

Applications

- Shopping malls
- Retail show rooms
- Hospitality etc.

Specification

- Recessed mounted die-casted sleek down lights for soft down lighting.
- Construction in die-cast aluminum frame.
- Fixture holding system using ss spring.
- Polyester powder coated.
- Constant current external LED driver is provided.

Electrical Data

	roduct Code	Cat. Ref.	Lamp Type	Nominal Voltage (Vac)	Mains Current In Amps. At 240 V	Power Factor
1	12538	BGSLO Sleek 4W WH SQ	LED	240	0.038	>0.50
1	12539	BGSLO Sleek 8W WH SQ	LED	240	0.032	>0.90
1	12540	BGSLO Sleek 15W WH SQ	LED	240	0.072	>0.90

Data subject to variation due to change/improvement in the design, materials and processes.

	DRAWN	VDS	25-04-2016	FOR -	
BAJAJ LUMINAIRES	CHECKED	SD		REV - 1	DATE-09-05-2017
Making the difference	APPROVED	DVRS		DRG.No	
Making the difference	DATA SHEET RELEASED ON DT-			BGSLO Sleek 4/8/15W WH SQ-001	