# **DURALED Well Glass** (BY300P)

### **DURALED Well Glass**





### Features:

- Energy-efficient: System efficacy of 110 lm/W, one on one replacement for 70W SON Well Glass
- Comfortable light: CRI of 80 to ensure better color rendering
- Optimal lighting effects: new light platform & optical design reduce
  20% glare
- Robust & Reliable: IP65 & IK 08 protection and 50K hours system life time
- Versatile applications: Multiple mounting options (Wall, Ceiling,
  Eyebolt )
- Wider Industry Application: Available with Dual Lumen Output

### **Product Specification Sheet**

Description	BY 300P		
System Lumen	3700* lm , 2700* lm		
ССТ	6500K, 4000K, 3000K		
CRI	> 80		
SDCM	< 5		
IP	65		
IK	08		
Mounting	Adjustable Bracket		
Efficacy	110 lm/W		
Surge protection	4 kV		
Life	L70B50 @ 50,000 hrs.		
Driver	Fixed output		
Housing	Single Piece Pressure Die Cast Housing		
THD	≤10%		
Serviceability	Class B (driver replaceable)		
Wattage	34W , 24W		
LILO	Optional		
Additional SPD	10 kV available on demand		


<sup>\*</sup>Lumen in NW & CW variant only

### **Application Areas**






# **Mounting Possibilities**



**Surface Mount** 



Ceiling Mount



Wall Mount

## **Ordering Data**

12 NC	Product Description	Qty. per Box	Spare Driver 12 NC
919515812315	BY300P LED 25S WW PSU S1 PC	8	441539003814
919515812316	BY300P LED 27S NW PSU S1 PC	8	441539003814
919515812317	BY300P LED 27S CW PSU S1 PC	8	441539003814
919515812318	BY300P LED 25S WW PSU S1 PC LILO	8	441539003814
919515812319	BY300P LED 27S NW PSU S1 PC LILO	8	441539003814
919515812320	BY300P LED 27S CW PSU S1 PC LILO	8	441539003814
919515812324	BY300P LED 35S WW PSU S1 PC	8	441539003815
919515812325	BY300P LED 37S NW PSU S1 PC	8	441539003815
919515812326	BY300P LED 37S CW PSU S1 PC	8	441539003815
919515812327	BY300P LED 35S WW PSU S1 PC LILO	8	441539003815

Note: Confirm 12NC with product manager before ordering