

# Essential SmartBright G2 BVP13X

Less Hassle, more saving  
Led Flood light

Rishi Agnihotri & Nitin Bahl  
Professional Lighting - India



# Essential SmartBright G2, LED Flood light

---



10W



20W



**Less Hassle, More Savings**

---

## Unique Selling Points:

- **Unique look and feel** : One large piece honeycomb light diffuser uniform and glare free light
- **Reliable Savings** : Up to 85% energy saving, compared with Philips Halogen lamps flood light
- **Robust**: IP65, IK06, Class I protection, life of 15k hours @Ta 25° C
- **Wide voltage range** : Operating voltage of 100 – 240V

# Features and benefits

## Use with peace of mind

- IK06 classification
- IP65 certified
- Wide operating voltage of 100 – 240V



**Less Hassle, More Savings**

## Long-lasting performance

- Designed for energy savings of up to 85% compared with conventional lighting
  - L70B50 15k hours\* with a Ta of 25Deg C
  - Designed for operations under diverse environment from -20°C to 40°C
- \*Designed to sustain 70% of initial lumen output (L70) at 15,000 hours of lifetime*

## High-quality materials and design

- Unique honeycomb diffuser for uniform lighting and low glare lighting
- Pressure die-cast housing offers excellent corrosion-resistance and robustness
- Color packing with USP's of the product highlighted

## Wide selection

- Multiple choice of color temperature –  
Warm white (3000k), Neutral (4000k) and Cool white (6500k)
- Multiple choice of lumen packages

# Essential SmartBright G2, LED Flood light

Precision aiming  
Dial/lock. Allen-  
key provided,  
user friendly



High quality honeycomb  
pattern light diffuser,  
anti-glare

IP65,  
Dust penetration-protected,  
jet water-proof

Die-cast Aluminum  
housing, sturdy design

Complies IEC60598, High temperature,  
High humidity test, low temperature start  
test etc..

**PHILIPS**

# Application



**Less Hassle, More Savings**



Signage



Façade




Security

Other applications : garden, footpath, car park...


# Package in full colour with USP's



# Mounting Instruction :



# Dimensions



Type	10W	20W
a (mm)	60	72
b (mm)	6.4	6.4
c (mm)	Ø8.5	Ø8.5



# Ordering information

Ordering code, 12NC	Product Description	MoQ	Packing box dimension (mm)	Gross Wt (Kg)	Net wt (Kg)	Outbox dimension (mm)	Outerbox GrossWt (Kg)
919515812550	BVP131 LED8/WW 10W 100-240V WB IN	12	143 x 121 x 30	0.35	0.30	264 x 213 x 182	4.60
919515812551	BVP131 LED8/NW 10W 100-240V WB IN	12	143 x 121 x 30	0.35	0.30	264 x 213 x 182	4.60
919515812552	BVP131 LED8/CW 10W 100-240V WB IN	12	143 x 121 x 30	0.35	0.30	264 x 213 x 182	4.60
919515812553	BVP132 LED16/WW 20W 100-240V WB IN	12	165 x 138 x 32	0.43	0.38	298 x 225 x 204	5.70
919515812554	BVP132 LED16/NW 20W 100-240V WB IN	12	165 x 138 x 32	0.43	0.38	298 x 225 x 204	5.70
919515812555	BVP132 LED16/CW 20W 100-240V WB IN	12	165 x 138 x 32	0.43	0.38	298 x 225 x 204	5.70

## Detailed Specification

Model name	Essential SmartBright G2	
Family code	BVP131	BVP132
Power	10W	20W
Lumen output	800lm	1600lm
CCT	3000K/4000K/6500K	
CRI	80	
System Efficacy	80lm/w	
Insulation classification	Class I	
Connection	250mm flying wire	
Volt/Frequency	220-240V/50-60Hz	
IP rating	IP65	
IK rating	IK06	
Surge protection	2KV	
Lifetime	15,000 hrs @Ta 25°C (L70B50)	
Ambient Temp	-20~40°C	
Dimension	138 x 117 x 27mm	159 x 134 x 28mm
Casing colour	Black	
Certificate	CE / IEC60598	

**Serviceability : Class C (Full product replacement)**

**Note : All are nominal values at Nominal operating voltage 220 -240V and will vary +/-10%**

