

Product data

General Characteristics

Cap-Base G24d-1 Cap-Base Information 2P 6500 hr Life to 10% failures Life to 50% failures 10000 hr ΕM LSF EM 2000h Rated, 99 % 3h cycle LSF EM 4000h Rated, 98 % 3h cycle LSF EM 6000h Rated, 92 % 3h cycle LSF EM 8000h Rated, 78 % 3h cycle

• Light Technical Characteristics

Color Code	865 [CCT of 6500K]
Color Rendering	80 Ra8
Index	
Color Designation	Cool Daylight
(text)	
Color Temperature	6500 K
Luminous Flux EM	840 Lm
25℃, Rated	
Luminous Flux EM	840 Lm
25℃, Nominal	
Lum Efficacy Rated	63 Lm/W
EM 25 °C	
LLMF EM 2000h	90 %
Rated	
LLMF EM 4000h	85 %
Rated	
LLMF EM 6000h	81 %
Rated	



MASTER PL-C 2 Pin

MASTER PL-C 13W/865/2P 1CT

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

LLMF EM 8000h	77 %
Rated	
Design Temperature	28 C
Chromaticity Coor-	313 -
dinate X	
Chromaticity Coor-	337 -
dinate Y	

• Electrical Characteristics

Lamp Wattage	13 W
Lamp Wattage EM	13 W
25 °C, Nominal	
Lamp Wattage EM	13.4 W
25℃, Rated	
Lamp Voltage EM	95 V
25℃	
Lamp Current EM	0.170 A
25℃	
Dimmable	No

• Environmental Characteristics

Energy Efficiency	В
Label (EEL)	
Mercury (Hg)	1.4 mg
Content	
Energy consumption	17 kWh
kWh/1000h	

Product Dimensions

Base Face to Base	97.7 (max) mm
Face A	
Insertion Length B	116.0 (max) mm
Overall Length C	138.4 (max) mm
Diameter D	27.1 (max) mm



MASTER PL-C 2 Pin

Diameter D1 27.1 (max) mm

• Product Data

Order code 927904886599 Full product code 927904886599

Full product name MASTER PL-C 13W/865/2P 1CT Order product name MASTER PL-C 13W/865/2P 1CT/

5X10CT

Pieces per pack 1
Packing configuration 5X10CT
Packs per outerbox 50

Warnings and Safety

• Use only with electromagnetic control gear

 Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position Bar code on pack - 8727900075458

EAN1

Bar code on inter- 8727900076356

mediate packing -

EAN2

8727900077339

Bar code on outerbox - EAN3

Logistic code(s) - 927904886599


12NC

ILCOS code FSQ-13/65/1B-I-G24d=1

Net weight per piece 0.049 kg

· Dimming is not possible

Dimensional drawing



MASTER PL-C 13W/865/2P 1CT

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
PL-C 13W/865/2P	97.7	116.0	138.4	27.1	27.1

2014, December 2 data subject to change



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.