



# **GreenPerform Sleek**

## DN296B LED12S-6500 PSU WH

Green Perform Sleek luminaire is designed for low dept false ceiling. Slim design with non-integral driver enables installation into low height false ceilings of different thickness and materials. Narrow rim semi-deep recessed design gives high quality lighting for designer ceilings. Highly efficient Electronic driver with high performance LED's ensures the longer life & high performance in this product category. Wide range of CCT's & Lumen packs suitable for various application.

### **Product data**

General Information	
Beam angle of light source	120 °
Light source color	865 cool daylight
Driver included	Yes
Optic type	120 [ Beam angle 120°]
Optical cover/lens type	Polycarbonate
Luminaire light beam spread	120°
Protection class IEC	Safety class I (I)
Flammability mark	F [ For mounting on normally flammable
	surfaces]
Warranty period	2 years
Material	Aluminum
Light source engine type	LED
Operating and Electrical	
Input Voltage	130-320 V
Input Frequency	50 Hz
Power Factor (Min)	0.95

Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Housing Material	Aluminum die-cast	
Optic material	Polycarbonate	
Optical cover/lens material	Polycarbonate	
Mounting device	Spring clip for recess mounting	
Color	White and black	
Approval and Application		
Ingress protection code	IP20 [ Finger-protected]	
Mech. impact protection code	IK02 [ 0.2 J standard]	
Surge Protection (Common/Differential) Surge protection level until 2.5 kV		
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux)	1200 lm	
Initial LED luminaire efficacy	110 lm/W	
Init. Corr. Color Temperature	6500 K	
Init. Color Rendering Index	>80	
Initial chromaticity	<5	

Datasheet, 2019, July 4 data subject to change

# **GreenPerform Sleek**

Initial input power	11 W
Power consumption tolerance	+/-10%
Over Time Performance (IEC C	Compliant)
Median useful life L70B50	50000 h
Application Conditions	
Ambient temperature range	0 to +45 ℃
Product Data	
Order product name	DN296B LED12S-6500 PSU WH

Order code	919515812856
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	919515812856
Net Weight (Piece)	0.280 kg







## **Warnings and Safety**

### Dimensional drawing





Indoor Luminaires



 $@ \ 2019 \ Signify \ Holding \ All \ rights \ reserved. \ Signify \ does \ not \ give \ any \ representation \ or \ warranty \ as \ to \ the \ accuracy \ or \ accuracy \ o$ completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any  $quotation\ or\ contract,\ unless\ otherwise\ agreed\ by\ Signify.\ Philips\ and\ the\ Philips\ Shield\ Emblem\ are\ registered$ trademarks of Koninklijke Philips N.V.