


CABLES



Document ID: TE/QMS/F/02



→ Flexible Bunched Copper Conductor

Insulation

Outer sheath

MULTICORE FLEXIBLE CABLE

DESIGN CODE : LDIS09CYUAY1024C0.5SA

Particulars	24 Core X 0.5 Sq.mm	
Name of Manufacturer	Polycab India Ltd	
Type of cable	YY	
Voltage Grade V	1100	
No of cores X size in sq.mm.	24 Core X 0.5 Sq.mm.	
Conductor		
a) Material	Plain annealed high conductivity flexible copper conductor as per Class 5 of IS 8130/2013, latest	
 b) Max. d.c. resistance of conductor at 20° C (ohm/km) 	39	
c) Shape of the conductor	Flexible Circular	
Insulation		
a) Material	PVC TYPE D as per IS 5831/1984, Latest	
b) Nominal thickness (mm)	0.6	
c) Core identification	As per Annexure-I	
Outer Sheath		
a) Material	Extruded PVC Type ST3 as per IS 5831/1984, Latest	
b) Nominal thickness (mm)	1.2	
c) Colour of outer sheath	Black	
Approx. overall diameter of the cable in mm	15.1+/-2	
Maximum conductor temperature under normal operating condition	70°C	
Maximum conductor temperature at the terminal of short circuit	160°C	
Electrical Parameters		
 a) Max. a.c. resistance of conductor at operating temperature (Ohm/Km) 	46.7	
b) High voltage test	3kV	
Continuous Current carrying capacities :-		
a) In Air at 40°C (A)	3.6	
Applicable Standard	IS 8130/2013, IS 5831/1984, IS 694/2010, etc. with latest up to date updates	
Minimum bending radius	8 times Overall diameter	



Fire Properties

a) Flammability test

Standard packing length

Printing

CABLES

As per IEC 60332-1-2 100 meter coil, 300 meter coil, 500 meter, 1000 meter (Higher quantity in wodden drum) POLYCAB <SIZE SQ.MM> 1100V IS : 694 <ISI LOGO> CM/L -2832257, HALOL - <CE MARKING>

Annexure-1				
Colour Scheme for Multicore flexible cable 6 core and above				
Sr. No	Printing No.	Basic Colour	Stripe	
1		Yellow	Green	
2	1	Black	-	
3	2	White	-	
4	3	Red	-	
5	4	Green	-	
6	5	Orange	-	
7	6	Blue	-	
8	7	White	Black	
9	8	Red	Black	
10	9	Green	Black	
11	10	Orange	Black	
12	11	Blue	Black	
13	12	Black	White	
14	13	Red	White	
15	14	Green	White	
16	15	Blue	White	
17	16	Black	Red	
18	17	White	Red	
19	18	Orange	Red	
20	19	Blue	Red	
21	20	Red	Green	
22	21	Orange	Green	
23	22	Black	Green	
24	23	Blue	Green	
25	24	White	Green	
26	25	Black	Orange	

Issued Date : 10/06/2021

Note:-The values given above are subject to tolerances as per the relevant standards www.polycab.com | Toll Free No - 1800 267 0008 | Email: enquiry@polycab.com