



FR-LSH MULTICORE FLEXIBLE CABLE

DESIGN CODE: LDIS09CYUAYL004C0.5S

Document ID: TE/QMS/F/02

Particulars		4 Core X 0.5 Sq.mm.
Name of Manufacturer		Polycab India Ltd
Type of cable		YY
Voltage Grade V		1100
No of cores X size in sq.mm.		4 Core X 0.5 Sq.mm.
Conductor		
a) Material		Plain annealed high conductivity flexible copper conductor as per Class 5 of IS 8130/2013, latest
b) Max. d.c. resistance of conductor at 20° C (ohm/km)		39
c) Shape of the conductor		Flexible Circular
Insulation		
a) Material		PVC TYPE D as per IS 5831/1984, Latest
b) Nominal thickness (mm)		0.6
c) Core identification		Red, Yellow, Blue and green-yellow
Sheath		
a) Material		Extruded FR-LSH PVC Type ST3 as per IS 5831/1984, Latest
b) Nominal thickness (mm)		0.9
c) Colour of outer sheath		Black
Approx. overall diameter of the cable in mm		6.9+/-2
Electrical Parameters		
Maximum conductor temperature under normal operating condition		70°C
Maximum conductor temperature at the terminal of short circuit		160°C
High voltage test		3kv
Continuous Current carrying capacities :-		
a) In Air at 40°C (A)		3.6
Applicable Standard		IS 8130/2013, IS 5831/1984, IS 694/2010, etc. with latest up to date updates
Minimum bending radius		8 times Overall diameter

FR-LSH properties		
a)	Oxygen Index	Min. 29% as per ASTM D-2863
b)	Temperature Index	Min. 250 Deg. C as per ASTM D-2863
c)	Smoke density ratting	Max. 60% as per ASTM D -2843
d)	Acid gas generation	Max. 20% as per IEC 60754-1
	Standard packing length	100 meter coil, 300 meter coil, 500 meter, 1000 meter (Higher quantity in wodden drum)
	Printing	POLYCAB FR-LSH<SIZE SQ.MM> 1100V IS : 694 <ISI LOGO> CM/L - 2832257, HALOL - <CE MARKING>