







**DESIGN CODE: LDIS09CYUAYL012C1.5S** 

## FR-LSH MULTICORE FLEXIBLE CABLE

Document ID: TE/QMS/F/02

| Document ID. 12/QIVIS/1/02   |                    | DESIGN CODE : EDISOSCI OATEOIZCI.SS   |  |
|--|--------------------|---|--|
| Particulars  |                    | 12 Core X 1.5 Sq.mm   |  |
| Name of Manufacturer   |                    | Polycab India Ltd   |  |
| Type of cable  |                    | YY  |  |
| Voltage Grade V  |                    | 1100  |  |
| No of cores X size in sq.mm.   |                    | 12 Core X 1.5 Sq.mm.  |  |
| Conductor  |                    |   |  |
| a) Material  |                    | Plain annealed high conductivity flexible copper conductor as per Class 5 of IS 8130/2013, latest |  |
| <ul><li>b) Max. d.c. resistance of cond<br/>(ohm/km)</li></ul>           | luctor at 20° C    | 13.3  |  |
| c) Shape of the conductor  |                    | Flexible Circular   |  |
| Insulation   |                    |   |  |
| a) Material  |                    | PVC TYPE D as per IS 5831/1984, Latest  |  |
| b) Nominal thickness (mm)  |                    | 0.6   |  |
| c) Core identification   |                    | As per Annexure-I   |  |
| Outer Sheath   |                    |   |  |
| a) Material  |                    | Extruded FR-LSH PVC Type ST3 as per IS 5831/1984, Latest  |  |
| b) Nominal thickness (mm)  |                    | 1.1   |  |
| c) Colour of outer sheath  |                    | Black   |  |
| Approx. overall diameter of the cal                                      |                    | 13.7+/-2  |  |
| Maximum conductor temperature under normal operating condition           |                    | 70°C  |  |
| Maximum conductor temperature at the terminal of short circuit           |                    | 160°C   |  |
| Electrical Parameters  |                    |   |  |
| <ul> <li>a) Max. a.c. resistance of cond temperature (Ohm/km)</li> </ul> | uctor at operating | 15.91   |  |
| b) High voltage test (kV)  |                    | 3   |  |
| Continuous Current carry   | ing capacities :-  |   |  |
| a) In Air at 40°C (A)  |                    | 15  |  |
| Applicable Standard  |                    | IS 8130/2013, IS 5831/1984, IS 694/2010, etc. with latest up to date updates                      |  |
| Minimum bending radius   |                    | 8 times Overall diameter  |  |
|  |                    |   |  |





## **FR-LSH Properties**

a) Oxygen Index

b) Temperature Index

c) Smoke density ratting

d) Acid gas generation

Standard packing length

**Printing** 

Min. 29% as per ASTM D-2863

Min. 250 Deg. C as per ASTM D-2863

Max. 60% as per ASTM D -2843

Max. 20% as per IEC 60754-1

100 meter coil, 300 meter coil, 500 meter, 1000 meter

(Higher quantity in wodden drum)

POLYCAB FR-LSH <SIZE SQ.MM> 1100V IS: 694 <ISI LOGO>

CM/L - 2832257, HALOL - <CE MARKING>

| Annexure-1  |              |              |        |  |  |
|---|--------------|--------------|--------|--|--|
| Colour Scheme for Multicore flexible cable 6 core and above |              |              |        |  |  |
| Sr. No  | Printing No. | Basic Colour | Stripe |  |  |
| 1   |              | Yellow       | Green  |  |  |
| 2   | 1            | Black        | -      |  |  |
| 3   | 2            | White        | -      |  |  |
| 4   | 3            | Red          | -      |  |  |
| 5   | 4            | Green        | -      |  |  |
| 6   | 5            | Orange       | -      |  |  |
| 7   | 6            | Blue         | -      |  |  |
| 8   | 7            | White        | Black  |  |  |
| 9   | 8            | Red          | Black  |  |  |
| 10  | 9            | Green        | Black  |  |  |
| 11  | 10           | Orange       | Black  |  |  |
| 12  | 11           | Blue         | Black  |  |  |
| 13  | 12           | Black        | White  |  |  |
| 14  | 13           | Red          | White  |  |  |
| 15  | 14           | Green        | White  |  |  |
| 16  | 15           | Blue         | White  |  |  |
| 17  | 16           | Black        | Red    |  |  |
| 18  | 17           | White        | Red    |  |  |
| 19  | 18           | Orange       | Red    |  |  |
| 20  | 19           | Blue         | Red    |  |  |
| 21  | 20           | Red          | Green  |  |  |
| 22  | 21           | Orange       | Green  |  |  |
| 23  | 22           | Black        | Green  |  |  |
| 24  | 23           | Blue         | Green  |  |  |
| 25  | 24           | White        | Green  |  |  |
| 26  | 25           | Black        | Orange |  |  |

Rev. No.: 00 Issued Date: 10/06/2021