



## INSTRUMENTATION CABLE

Document ID: TE/QMS/F/02

CABLE CODE: ICIS04CYSWYL003C1.5SA002S

| Particulars   | 3 Core X 1.5 sq mm                                   |
|---|--|
| Name of Manufacturer                                    | POLYCAB INDIA LTD                                    |
| Type of Cable   | Overall Screened                                     |
| No of Elements X Size in mm <sup>2</sup>                | 3C X 1.5   |
| Voltage Grade (V)                                       | 300/500  |
| <b>Conductor</b>  |  |
| a) Material   | Plain Stranded Copper (Class-2) as per IS: 8130/2013 |
| b) Maximum D.C. resistance of conductor at 20° C (Ω/km) | 12.1   |
| c) Shape of conductor                                   | Stranded Circular                                    |
| <b>Insulation</b>                                       |  |
| a) Material   | PVC Type A as per IS:5831                            |
| b) Minimum Thickness mm                                 | 0.44   |
| c) Pair/Triad identification                            | Red, Yellow & Blue                                   |
| <b>Collective Screen</b>                                |  |
| a) Material   | Aluminium mylar tape                                 |
| b) Nominal Thickness mm                                 | 0.018  |
| c) Material of Drain Wire                               | Flexible ATC   |
| d) Size of Drain Wire (Approx.)                         | 0.5 mm <sup>2</sup> (16/0.2 mm)                      |
| <b>Inner sheath</b>                                     |  |
| a) Material   | Extruded PVC Type ST1 to IS: 5831                    |
| b) Minimum Thickness mm                                 | 0.3  |
| <b>Armouring</b>  |  |
| a) Material   | Galvanised Steel                                     |
| b) Type of armouring                                    | Round Wire   |
| c) Nominal size of armour (mm)                          | 0.9  |
| d) Tolerance on armour dimensions                       | ± 0.030 mm   |
| <b>Outer sheath</b>                                     |  |
| a) Material   | Extruded FR-LSH PVC Type ST1 to IS: 5831             |
| b) Thickness mm   | 1.24 (Min.)  |
| c) colour of sheath                                     | Blue   |
| <b>FR-LSH PROPERTIES</b>                                |  |
| a) Oxygen Index   | Min. 29% as per ASTM D- 2863                         |
| b) Temperature Index                                    | Min. 250 Deg.C as per ASTM D- 2863                   |
| c) Smoke Density Rating                                 | Max. 60% as per ASTM D- 2843                         |

Rev.No.:00

Issued Date:02/04/2018

Note: -The values given above are subject to tolerances as per the relevant standards.

www.polycab.com | Toll Free No - 1800 267 0008 | Email: enquiry@polycab.com

|  |   |
|--|---|
| d) Acid Gas Generation   | Max. 20% as per IEC- 754- 1   |
| e) Flammability Test   | As per IEC:332-I  |
| Maximum conductor temperature under normal operating conditions °C | 70  |
| Minimum bending radius   | 12 times Overall diameter   |
| <b>Electrical Parameters</b>                                       |   |
| a) Mutual capacitance nf/km  | <250  |
| b) Insulation resistance MΩ/km                                     | 10  |
| c) Inductance to resistance ratio (L/R) μH/Ω                       | <40   |
| d) Dielectric strength for 1 minute (H.V Test) kV                  | 2   |
| Max. tensile strength for Cables pulled with stocking (Newtons)    | 9 x D <sup>2</sup> , D is the cable OD in mm  |
| Approximate Overall diameter of cable mm                           | 11.5 ± 2.0  |
| Applicable Standard  | Generally, as per IS 1554 Part I/88 & BSEN 50288-7  |
| Standard Drum Length (Mtr.)  | 1000 ± 5%   |
| Non-Standard Drum Length (Mtr.)                                    | Maximum 5% of order quantity  |
| Embossing  | POLYCAB 300/500 VOLTS GRADE FR-LSH  |
| Printing   | YEAR POLYCAB 300/500 VOLTS GRADE FR-LSH CABLE SIZE<br>SCREENED with SEQUENTIAL LENGTH MARKING at EVERY ONE METER INTERVAL |