



LT XLPE CABLE

Document ID: TE/QMS/F/02

DESIGN CODE: LVIS09CXSFYL004C185SA001S

Particulars	4 Core X 185 Sq.mm
Name of Manufacturer	Polycab India Ltd.
Type of cable	2XFY
Voltage Grade V	1100
No of cores X size in sqmm	4 Core X 185 Sq.mm
Conductor	
a) Material	Plain annealed Copper as per Class 2 of IS:8130/2013
b) Max. d.c. resistance of conductor at 20° C (ohm/km)	0.0991
c) Shape of the conductor	Stranded Compacted Sector
Insulation	
a) Material	XLPE as per IS 7098(Pt-1)/88, Latest
b) Nominal thickness (mm)	1.6
c) Core Identification	Red, Yellow, Blue & Black
Inner Sheath	
a) Material	Extruded PVC Type ST2 as per IS:5831/84
b) Minimum thickness (mm)	0.5
Armouring	
a) Material	Galvanised Steel
b) Type of armouring	Flat Strip
c) Nominal size of armour (mm)	4.0 x 0.8
d) Tolerance on armour dimensions	± 10%
Outer Sheath	
a) Material	Extruded FR-LSH PVC Type ST2 as per IS:5831/84
b) Thickness (mm)	2.04 (Min.)
c) Colour of outer sheath.	Black
Electrical Parameters	
a) Max. a.c. resistance of conductor at 90° C (ohm/km)	0.128
b) Calculated Cable reactance (ohm/km)	0.072
c) Impedance of cable (ohm/km)	0.147
d) Approx. Cable Capacitance (mfd/km)	0.63
Maximum conductor temperature under normal operating conditions	90°C

Rev.No.:00

Issued Date:02/04/2018

Note: -The values given above are subject to tolerances as per the relevant standards.

www.polycab.com | Toll Free No - 1800 267 0008 | Email: enquiry@polycab.com

Maximum conductor temperature at the termination of short circuit	250°C
Short Circuit rating of conductor for the duration of 1 sec (kA)	26.47
Continuous Current carrying capacities :-	
(a) In Ground at 30°C (A)	362
(b) In Air at 40°C (A)	422
Applicable Standard	IS 8130/2013, IS 7098 Part I/88, IS 5831/84, IS 3975/1999 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm	48.5 +/-2.0
Minimum bending radius	12 times Overall diameter
Max. Tensile strength	
(i) for Cables pulled with stocking (Newtons)	$9 \times D^2$, D is the cable OD in mm
(ii) for Cables pulled with pulling eyes (N)	37000
Embossing	POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH
Printing	YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval.
Standard Drum Length (Mtr.)	500 ± 5%
Non- Standard Drum Length (Mtr.)	Maximum 5% of order quantity
FR-LSH PROPERTIES	
a) Oxygen Index	Min. 29% as per ASTM D- 2863
b) Temperature Index	Min. 250 Deg.C as per ASTM D- 2863
c) Smoke Density Rating	Max. 60% as per ASTM D- 2843
d) Acid Gas Generation	Max. 20% as per IEC- 754- 1
e) Flammability Test	As per IEC:332-I