



LT XLPE CABLE

Document ID:TE/QMS/F/02

DESIGN CODE: LVIS09CXSFYL3.5C240SA001S

Particulars		3.5 Core X 240 Sq.mm
Name of Manufacturer		Polycab India Ltd
Type of cable		2XFY
Voltage Grade V		1100
No of cores X size in sqmm		3.5 Core X 240 Sq.mm
Conductor		
a) Material	Plain annealed Copper as per Class 2 of IS:8130/2013, latest	
b) Max. D.C. resistance of conductor at 20° C (ohm/km)	Main	0.0754
	Neutral	0.153
c) Shape of the conductor	Stranded Compacted Sector	
Insulation		
a) Material	XLPE as per IS 7098(Pt-1)/88, Latest	
b) Nominal thickness (mm)	Main	1.7
	Neutral	1.2
c) Core identification	Red, Yellow, Blue, Black	
Inner Sheath		
a) Material	Extruded PVC Type ST2 as per IS:5831/84	
b) Minimum thickness (mm)	0.6	
Armouring		
a) Material	Galvanised Steel	
b) Type of armouring	Flat Strip	
c) Nominal size of armour (mm)	4.0 x 0.8	
d) Tolerance on armour dimensions	± 10%	
Outer Sheath		
a) Material	Extruded FR-LSH PVC Type 'ST2' as per IS:5831	
b) Thickness (mm)	2.04 (Min.)	
c) Colour of outer sheath.	Black	
Electrical Parameters		
a) Max. a.c. resistance of conductor at 90° C (ohm/km)	0.0988	
b) Calculated Cable reactance (ohm/km)	0.0713	

Rev.No.:00

Issued Date:02/04/2018

Note: -The values given above are subject to tolerances as per the relevant standards.

www.polycab.com | Toll Free No - 1800 267 0008 | Email: enquiry@polycab.com

c) Impedance of cable (ohm/km)	0.122
d) Approx. Cable Capacitance (mfd/km)	0.67
Maximum conductor temperature under normal operating conditions	90°C
Maximum conductor temperature at the termination of short circuit	250°C
Short Circuit rating of conductor for the duration of 1 sec (kA)	34.34

Continuous Current carrying capacities :-

a) In Ground at 30°C (A)	418
b) In Air at 40°C (A)	500
Applicable Standard	IS 7098 Part I/88, IS 8130, IS 5831, IS 3975 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm	50.5 +/- 2.0
Minimum bending radius	12 times Overall diameter
Max. Tensile strength	
i) for Cables pulled with stocking (Newtons)	9 x D ² , D is the cable OD in mm
ii) for Cables pulled with pulling eyes (N)	42,000
Embossing	POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH
Printing	YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval.
Standard Drum Length (Mtr.)	500 ± 5%
Non- Standard Drum Length (Mtr.)	Maximum 5% of order quantity

FR-LSH Properties

a) Oxygen Index	Min. 29% as per ASTM D- 2863
b) Temperature Index	Min. 250 Deg.C as per ASTM D- 2863
c) Smoke Density Rating	Max. 60% as per ASTM D- 2843
d) Acid Gas Generation	Max. 20% as per IEC- 754- 1
e) Flammability test	As per IEC:332-I