


CABLES



Transparent PVC insulation

SPEAKER CABLE

Document ID: TE/QMS/F/02

DESIGN CODE : SPPB09CYUAYT002C.18S

Description		2C X 23/38 AWG
Manufacturer Name		Polycab India Limited
Type of cable		Twin Parallel Speaker Cable
Rated Voltage		Up to & Including 1100 V
Conductor		
a)	Material	Oxygen free Copper as per Class 6 of IS: 8130/84,latest
b)	Nominal dia of each wires size (mm)	0.101 (38 AWG)
c)	No of wires	23
d)	Nominal cross sectional area (Sq.mm)	0.185
e)	Shape of conductor	Circular Bunched
f)	Max. D.C Cond. Resistance at 20 Deg. C. (Ohm/km)	105.5
Insulation		
a)	Material	Transparent PVC
b)	Nominal Thickness in mm.	0.80
c)	Overall Diamension (w x h) (Approx.) (mm)	4.30 X 2.30
d)	Core Identification	Natural & Natural-Blue
General and Environmental Characteristics		
a)	Temp Range operation storage \degree C	-10° C + 60° C
b)	Temp Range installation °C	-0°C+50°C
c)	Max. conductor temp. under normal operating conditions ° C	70°C
Stanadrd Packing Length (M)		90 Meter
Standards to which the cables confirm		Generally as per IS 8130/84,IS 694,/IS 5831 etc. with latest up to date amendments

Rev. No.: 00

Issued Date : 23/12/2022

Note:-The values given above are subject to tolerances as per the relevant standards.

www.polycab.com | Toll Free No - 1800 267 0008 | Email: enquiry@polycab.com