



MLFB-Ordering data: **1LE7503-3AB03-5JA4**

Frame size: **3155**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]±10%	Δ/Y	f [Hz]±5%	P [kW]	I [A]	n [1/min]	M [kgf.m]	M [Nm]	NOM. EFF at ... load [%] *			Power factor at ... load *			I <sub>A</sub> /I <sub>N</sub> I <sub>L</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>r</sub> /T <sub>N</sub>	M <sub>v</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
415	Δ	50	110.00	186.00	1488	72.0	706.0	95.5	95.4	94.3	0.86	0.82	0.74	7.3	2.6	2.9	IE3
Data subject to tolerance as per IS 12615 / IEC 60034-1								SF: 1.00			*sinusoidal feed						
Environmental conditions : -20 °C to +50 °C / 1000.0 m								locked rotor withstand time (hot / cold) : 20.0 s / 31.0 s									

Mechanical data			Terminal box	
Sound pressure level 50Hz   60Hz	80 dB(A)	83 dB(A)	Terminal box position	Top
Type of construction	IM B35 / IM 2001		Material of terminal box	Cast iron
Bearing DE   NDE	6319 C3	6319 C3	Type of terminal box	TB1 Q01
Type of bearing	Locating (fixed) bearing, NDE		Contact screw thread	M12
Lubricants	Esso Unirex N3		Max. cross-sectional area	240.0 mm <sup>2</sup>
Regreasing device	Yes (standard)		Cable diameter from ... to ...	38.0 mm - 45.0 mm
Grease nipple	M10x1 DIN 3404 A		Cable entry	2xM63x1,5
Relubrication interval/quantity (AS BS)	40 g   40 g 6000 h		Cable gland	2 Plugs
Bearing lifetime	50000 h			
Degree of protection	IP55			
Vibration severity grade	A (Standard)			
Insulation	155(F) utilized to 130(B)			
Duty type	S1			
Direction of rotation	Bidirectional			
Frame material	Cast iron			
Data of anti condensation heating	- / -			
Coating (paint finish)	Standard paint finish			
Color, paint shade	RAL7030			
Motor protection	(A) without			
Method of cooling	IC411 - Self ventilated, surface cooled			
Forced ventilation motor details	- / -			
Weight in kg, without optional accessories	765 kg			
Rotor weight in kg	209,8 kg			
Moment of inertia	Rotor GD <sup>2</sup>	2.19555 kg m <sup>2</sup>	8.7822 kgf.m <sup>2</sup>	

### Notes

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / nominal current      M<sub>v</sub>/M<sub>N</sub> = break down torque / nominal torque  
M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / nominal torque