

LV HRC fuse element, NH3, In: 400 A, gG, Un AC: 500 V, Un DC: 440 V, Front indicator, live grip lugs



| Model | |
|--|---------------------|
| Product designation | LV HRC fuse link |
| Design of the product | With blade contacts |
| Design of an identification indicator | Front indicators |
| General technical data | |
| Size of fuse system / acc. to DIN EN 60269-1 | NH3 |
| Operating class of the fuse link | gG |
| Supply voltage | |
| • at AC / rated value | 500 V |
| • at DC | 440 V |
| Electricity | |
| Current / at AC / rated value | 400 A |
| Certificates | |



GL

Further information**Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA3360-0RC>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3NA3360-0RC>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA3360-0RC**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>