

LV HRC fuse element, NH3, In: 500 A, gG, Un AC: 690 V, Un DC: 440 V, Front indicator, live grip lugs



### Model

Product designation	LV HRC fuse link
Design of the product	With blade contacts
Design of an identification indicator	Front indicators

### General technical data

Size of fuse system / acc. to DIN EN 60269-1	NH3
Operating class of the fuse link	gG
Type of voltage	AC/DC
Current / at AC / rated value	500 A
Supply voltage	
• at AC / rated value	690 V
• at DC	440 V

### Certificates



GL

**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA3365-6RC>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3NA3365-6RC>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA3365-6RC](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA3365-6RC)**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>



