

LV HRC fuse link, NH000, In: 10 A, gG, Un AC: 500 V, Un DC: 250 V, Combination indicator, non-insulated grip lugs

| Model | |
|---------------------------------------|--------------------|
| Product designation | LV HRC fuse link |
| Design of an identification indicator | Combination alarms |

| General technical data | |
|--|-------|
| Size of fuse system / acc. to DIN EN 60269-1 | NH000 |
| Operating class of the fuse link | gG |
| Supply voltage | |
| • at AC / rated value | 500 V |
| • at DC | 250 V |

| Electricity | |
|-------------------------------|------|
| Current / at AC / rated value | 10 A |

| Certificates | |
|-------------------|-------|
| Shipping Approval | other |

[sonstig](#)



GL

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NA7803-0RC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NA7803-0RC/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7803-0RC

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>