

LV HRC fuse link, NH000, In: 16 A, gG, Un AC: 500 V, Un DC: 250 V, Combination indicator, non-insulated grip lugs

Model	
Product designation	LV HRC fuse link
Design of an identification indicator	Combination alarms

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH000
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	500 V
• at DC	250 V

Electricity	
Current / at AC / rated value	16 A

Certificates	
Shipping Approval	other

[sonstig](#)



GL

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NA7805-0RC>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3NA7805-0RC/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA7805-0RC](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7805-0RC)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>