

LV HRC fuse link, NH000, In: 50 A, gG, Un AC: 500 V, Un DC: 250 V, Combination indicator, non-insulated grip lugs

| Model                                 |                    |
|---------------------------------------|--------------------|
| Product designation                   | LV HRC fuse link   |
| Design of an identification indicator | Combination alarms |

| General technical data                       |       |
|--|-------|
| Size of fuse system / acc. to DIN EN 60269-1 | NH000 |
| Operating class of the fuse link             | gG    |
| Supply voltage                               |       |
| • at AC / rated value                        | 500 V |
| • at DC                                      | 250 V |

| Electricity                   |      |
|-------------------------------|------|
| Current / at AC / rated value | 50 A |

| Certificates      |       |
|-------------------|-------|
| Shipping Approval | other |

[sonstig](#)



GL

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NA7820-0RC>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3NA7820-0RC/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA7820-0RC](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7820-0RC)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>