SIEMENS

Data sheet

3NE4330-6B

SITOR fuse link, with female thread on both sides, In: 315 A, aR, Un AC: 800 V, Un DC: 440 V, front indicator



Model	
Product brand name	SENTRON
Product designation	SITOR fuse link
Design of the product	With female thread on both sides
Design of an identification indicator	front indicator
Design of the switching contact	With female thread on both sides, silver-plated
Design of the fuse link	Fuses for special applications

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	others
Operating class of the fuse link	aR
Diken-export / Let-through current	DS_3NE_3_1500_aR_315
circuit-breaker / Design	3NE
Varying load factor (WL)	0.85
Supply voltage	
• at AC / rated value	800 V
• at DC	440 V
Switching capacity	

Switching capacity current

• acc. to IEC 60947-2 / rated value	100 kA
Dissipation	
Power loss [W]	120 W
Power loss [W] / for rated value of the current / at AC	120 W
/ in hot operating state / per pole	
Electricity	
Tripping residual / rated value / derated current / at 40 Cel	315 A
Current / at AC / rated value	315 A
Diken-export / Let-through energy	DE_3NE_3_1500_aR_315
Product details	
Product description	Not non-interchangeable
Mechanical Design	
Mounting position	Any, preferably vertical
Environmental conditions	
Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity
Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F
Declaration of Conformity other	
<i>c c</i>	Miscellaneous

urther information

EG-Konf.

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE4330-6B

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NE4330-6B

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE4330-6B

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications



