

ISOLATOR 63A DOUBLE POLE



Figure similar

Model	
product brandname	SENTRON
Product designation	On/Off switches
Type of light source	Not applicable
Mounting type / for light source	Not applicable
Design of the switching function	Switch disconnecter
General technical data	
Number of poles	2
Short-circuit current rating	10 kA
Type of voltage	AC
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.196 kA
Main circuit	
Operating voltage / rated value	440 V

Operating current / rated value	63 A
---------------------------------	------

### Appearance

Color / of the lens	Not applicable
---------------------	----------------

### Product details

Product component / Signal lamp	No
---------------------------------	----

### Product function

Product function / positive opening (acc. to DIN VDE 0113)	No
--	----

### Number

Number of NC contacts	0
Number of NO contacts	2
Number of CO contacts	0

### Mechanical Design

Height	89.8 mm
Depth	74.5 mm
Installation depth	70 mm
Number of width units	2

<b>General Product Approval</b>	<b>Declaration of Conformity</b>
---------------------------------	----------------------------------



### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TL1263-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/5TL1263-0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TL1263-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TL1263-0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

