

Almaredge BI

General purpose soluble metalworking fluid

Description

Castrol Almaredge™ BI is a general purpose soluble metalworking fluid which is chlorine and boron-free. It contains a unique additive package that provides good lubrication properties and performs well in a wide water range.

Almaredge BI can be used in single sump machines as well large systems.

Application

Almaredge BI is a versatile product recommended for general machining on low-medium alloy steel and aluminium alloys.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding						
Milling, Turning (general ,machining)	ü	ü ü	ü	ü ü		ü
Drilling	ü	ü ü	ü	ü ü		ü
Reaming, Tapping	ü	ü ü	ü	ü		ü
Broaching				ü		ü

Advantages

- Boron free for environmental compliance and improved residue characteristics
- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Versatile product suitable for wide range of materials and operations
- Low foam in recommended water conditions

Typical Characteristics

Name	Method	Units	Almaredge BI
Concentrate	-	-	-
Appearance	Visual	-	Amber
Mineral oil content	Calculated	Wt%	> 60
Emulsion	-	-	-
Appearance	Visual	-	Milky
pH (5%)	DIN 51 361 / ASTM E70-97	-	9.5
Refractometer Factor	-	-	1.0

Typical Physical Characteristics

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives		ü		ü	

Recommended Concentrations

General Machining 4 - 7%

Drilling 5 - 7%

Reaming and tapping 7 - 10%

Water range 50 - 400 ppm CaCO

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Almaredge BI

12 May 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India

Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: customer-care.india@castrol.com

www.castrol.com/industrial