

## DX<sup>3</sup> isolators

ISs for AC applications upto 125A



4065 00

4065 10

4065 20

Technical characteristics p. 45

Isolators for AC applications upto 125 A  
 ISI marked as per IEC 60947-3  
 Integrated label holder  
 Ergonomic red color dolly  
 Sliding bottom clamp  
 Double break mechanism  
 Improved air channels  
 Color coded On/Off indication on dolly  
 Biconnect lower terminals  
 IP 20 protected terminals  
 Sliding shutters

Pack	Cat.Nos	Isolators	Number of modules
		<b>2 pole 415 V<math>\sim</math></b>	
		Nominal rating In (A)	
1/5/60	<b>4065 00</b>	32	2
1/5/60	<b>4065 01</b>	40	2
1/5/60	<b>4065 02</b>	63	2
1/5/60	<b>4065 04</b>	100	2
1/5/60	<b>4065 05</b>	125	2
		<b>3 pole 415 V<math>\sim</math></b>	
1/40	<b>4065 09</b>	32	3
1/40	<b>4065 10</b>	40	3
1/40	<b>4065 11</b>	63	3
1/40	<b>4065 13</b>	100	3
1/40	<b>4065 14</b>	125	3
		<b>4 pole 415 V<math>\sim</math></b>	
1/32	<b>4065 18</b>	32	4
1/32	<b>4065 19</b>	40	4
1/32	<b>4065 20</b>	63	4
1/32	<b>4065 22</b>	100	4
1/32	<b>4065 23</b>	125	4

## DX<sup>3</sup> RCCBs

RCCBs for AC applications upto 63 A



4118 51

4118 77

4118 93

Technical characteristics p. 46-51

ISI marked as per IS 12640-1  
 Integrated label holder  
 Ergonomic Grey color dolly  
 Sliding bottom clamp  
 Color coded On/Off indication on dolly  
 Biconnect lower terminals  
 IP 20 protected terminals  
 35 sq mm terminals  
 Sliding shutters

Pack	Cat.Nos	DX <sup>3</sup> RCCBs	Number of modules
		<b>2 pole 240 V<math>\sim</math></b>	
		<b>30 mA</b>	
		Nominal rating In (A)	
1/5/60	<b>4118 51</b>	25	2
1/5/60	<b>4118 52</b>	40	2
1/5/60	<b>4118 53</b>	63	2
		<b>100 mA</b>	
1/5/60	<b>4118 56</b>	25	2
1/5/60	<b>4118 57</b>	40	2
1/5/60	<b>4118 58</b>	63	2
		<b>300 mA</b>	
1/5/60	<b>4118 61</b>	25	2
1/5/60	<b>4118 62</b>	40	2
1/5/60	<b>4118 63</b>	63	2
		<b>4 pole 415 V<math>\sim</math></b>	
		<b>30 mA</b>	
1/32	<b>4118 76</b>	25	4
1/32	<b>4118 77</b>	40	4
1/32	<b>4118 78</b>	63	4
		<b>100 mA</b>	
1/32	<b>4118 81</b>	25	4
1/32	<b>4118 82</b>	40	4
1/32	<b>4118 83</b>	63	4
		<b>300 mA</b>	
1/32	<b>4118 86</b>	25	4
1/32	<b>4118 87</b>	40	4
1/32	<b>4118 88</b>	63	4
		<b>4 pole 415 V<math>\sim</math>, A-S</b>	
		<b>300 mA</b>	
1/5/60	<b>4118 91</b>	25	4
1/5/60	<b>4118 92</b>	40	4
1/5/60	<b>4118 93</b>	63	4
		<b>2 pole 240 V<math>\sim</math>, HPI</b>	
		<b>30 mA</b>	
1/5/60	<b>4118 71</b>	25	2
1/5/60	<b>4118 72</b>	40	2
1/5/60	<b>4118 73</b>	63	2
		<b>4 pole 415 V<math>\sim</math>, HPI</b>	
		<b>30 mA</b>	
1/32	<b>4118 96</b>	25	4
1/32	<b>4118 97</b>	40	4
1/32	<b>4118 98</b>	63	4

# DX<sup>3</sup> RCDS

technical data for DX<sup>3</sup> RCDs

Specification	RCCB		
	Type AC	Type A-S	Type Hpi
	IS 12640 (part 1) 2008 IEC 61008 - 1	IEC 61008 - 1 EN 61008 - 1	EN 61008 - 1 IEC 61008 - 1
<b>No. of modules</b>			
- Double pole	2	2	2
- Four pole	4	4	4
<b>Electrical characteristics</b>			
<b>Nominal rating I<sub>n</sub> (A)</b>			
- Double pole	25, 40, 63, 80, 100	63, 80	25, 40, 63, 80
- Four pole	25, 40, 63, 80, 100	25, 40, 63, 80	25, 40, 63, 80
<b>Rated sensitivity (mA)</b>			
- Double pole	30, 100, 300	300	30
- Four pole	30, 100, 300	300	30
<b>Rated frequency (Hz)</b>	50 / 60	50 / 60	50 / 60
<b>Rated operating voltage U<sub>e</sub> (V AC)</b>			
- Double pole	230	230	230
- Four pole	230 / 415	400	400
<b>Minimum operating voltage (V AC)</b>	12	12	12
<b>Minimum operating voltage for test button (V AC)<sup>(1)</sup></b>			
- Double pole	170	170	170
- Four pole	196	196	196
<b>Rated insulation voltage U<sub>i</sub> (V AC)</b>			
- Double pole	250	250	250
- Four pole	500	500	500
<b>Rated impulse withstand voltage U<sub>imp</sub> (kV)</b>	6	6	6
<b>Breaking capacity</b>	As per IS 12640 (part 1) 2008, IEC 61008 - 1		
<b>Rated making &amp; breaking capacity (I<sub>m</sub>)</b>			
- Up to 40 A	500 A	-	500 A
- From 63 A and above	10 x I <sub>n</sub>	630 A	630 A
<b>Rated residual making &amp; breaking capacity (I<sub>Δm</sub>)</b>			
- Up to 40 A	1000 A	-	1000 A
- From 63 A and above	1000 A	1000 A	1000 A
<b>Rated conditional short circuit current (I<sub>nc</sub>)</b>	10000 A	10000 A	10000 A
<b>Rated conditional residual short circuit current (I<sub>Δc</sub>)</b>	10000 A	10000 A	10000 A
<b>Rated service short circuit capacity (I<sub>cs</sub>)</b>	-	-	-
<b>Rated short circuit capacity (I<sub>cn</sub>)</b>	-	-	-
<b>Operating temperature (°C)</b>	- 25 to 70	- 25 to 70	- 25 to 70
<b>Endurance (0.C cycle)</b>			
- Mechanical	20,000	20,000	20,000
- On load at $i_n \times \cos \phi = 0.9$	10,000	10,000	10,000
- Via test button	2,000	2,000	2,000
- By fault current (sensitivity)	2,000	2,000	2,000
<b>Testing</b>	By pressing test button grey dolly will come to OFF position It is recommended to test RCCB once a month	By pressing test button grey dolly will come to OFF position It is recommended to test RCCB once a month	By pressing test button, grey dolly will come to OFF position It is recommended to test RCCB once a month
<b>Fault indication</b>			
- Earth leakage	Grey dolly will come to OFF position	Grey dolly will come to OFF position	Grey dolly will come to OFF position
- Overload and shortcut	-	-	-
<b>Resetting</b>	Switch on grey dolly	Switch on grey dolly	Switch on grey dolly
<b>Terminals</b>			
- Rigid	1 - 35 sq. mm	1 - 35 sq. mm	1 - 35 sq. mm
- Flexible	1 - 25 sq. mm	1 - 25 sq. mm	1 - 25 sq. mm
<b>Type of protection</b>			
Earth leakage	•	•	•
Overload	-	-	-
Short circuit	-	-	-
<b>Add on electrical accessories*</b>			
Auxiliary	•	•	•
Fault signaling	•	•	•
Shunt trip	•	•	•
Under voltage	•	•	•
Over voltage	•	•	•

\* - Accessories are mounted on the left hand side of the product.  
At a time a maximum of three accessories can be mounted.

<sup>(1)</sup> - Between phase and neutral

RCBO				
	Type AC	Type AC - 2 & 4 modules	Type Hpi	Type A
	IS 12640 (part 2) 2008 IEC 61009 - 1	NFC 61 - 410 EN 61009 - 1 IEC 61009 - 1	EN 61009 - 1 IEC 61009 - 1	EN 61009 - 1 IEC 61009 - 1
	4	2	2	-
	7	4	-	4
	6, 10, 16, 25, 32, 40, 63	6, 10, 16, 20, 25, 32	25, 32, 40	25, 32, 40
	16, 25, 32, 40, 63	10, 16, 20, 25, 32	-	-
	30, 100, 300	30, 300	30	30, 300
	30, 100, 300	-	-	-
	50	50	50 / 60	50 / 60
	230	230	230	-
	415	415	-	415
	12	12	12	12
	170	170	170	-
	196	196	-	196
	500	250	250	-
	500	500	-	500
	4	6	6	6
	<b>As per IS 12640 (part 2) 2008, IEC 61009 - 1</b>			
	10000 A	6000 A	6000 A	6000 A
	10000 A	-	-	-
	10000 A	3000 A	3000 A	3000 A
	10000 A	-	-	-
	-	-	-	-
	-	-	-	-
	7500 A	6000 A	6000 A	6000 A
	10000 A	6000 A	6000 A	6000 A
	- 25 to 70	- 25 to 70	- 25 to 70	- 25 to 70
	20,000	20,000	20,000	20,000
	10,000	10,000	10,000	10,000
	1,000	1,000	1,000	1,000
	1,000	1,000	1,000	1,000
	By pressing test button, black dolly will come to OFF position It is recommended to test RCBO once a month	By pressing test button, black dolly will come to OFF position It is recommended to test RCBO once a month	By pressing test button, black dolly will come to OFF position It is recommended to test RCBO once a month	By pressing test button, black dolly will come to OFF position It is recommended to test RCBO once a month
	Black & blue dolly will come to OFF position	Black dolly will come to OFF position & blue indicator will appear on front face window	Black dolly will come to OFF position & blue indicator will appear on front face window	Black dolly will come to OFF position & blue indicator will appear on front face window
	Black dolly will come to OFF position	Black dolly will come to OFF position	Black dolly will come to OFF position	Black dolly will come to OFF position
	Switch on black dolly	Switch on black dolly	Switch on black dolly	Switch on black dolly
	1 - 35 sq. mm	0.75 - 16 sq. mm	0.75 - 16 sq. mm	0.75 - 16 sq. mm
	1 - 25 sq. mm	0.75 - 10 sq. mm	0.75 - 10 sq. mm	0.75 - 10 sq. mm
	•	•	•	•
	•	•	•	•
	•	•	•	•
	•	•	•	•
	•	•	•	•
	•	•	•	•
	•	•	•	•
	•	•	•	•